

Carrier tape forming machine

Features:

1. Feeding system:with brake automatic tension feeding system,optical sensor sending signal , PLC control , speed adjustable.
2. Feeding buffer : feeding buffer could solve the problem of tape bending and damage caused by unstable feeding .
3. Preheating system:PLC preheating control temperature system, improve forming speed avoid the forming tape have air hole or bad tapes.
4. Forming system:the tape preheating under the function of vacuum and hot air , Continuous rotary mould and rapidly molding .Guide by guidance mechanism releases from mould become expect pocket .
5. Cutting system: equip with Guidance mechanism and precision cutting wheel, cut off redundant tapes ,the carrier tape will be with right width size.offcut tapes will automatic running out.
6. Punching structure :high precision machinery working structure , Can continuous high-speed rushed out accord with EIA standard chain hole,make sure hole chain smooth .
7. Rolling buffer :automatic tension buffer PLC control, the speed could adjustable , make sure that the products not damaged .
- 8.Rolling system:carrier tape complete manufacturing ,According to the hierarchical order neat around the tray, speed adjustable.



Specification :

Model	SM-8000F
Feeding tape width	8-27mm
Capacity	600m/h
Products standard	EIA standard
Weight	290KG
Dimension	140*68*230cm
Power supply	220V 50-60HZ,1.2KWA Reliable grounding
Air supply	The compressed air inlet pressure not less than 0.6 MPa ,Flow rate is not less than 2500 l/H,No oil , water and dust
Environmental requirement	Temperature below 28°C, workshop no dust.

Factory photos :

Address:Rm B306, Build A, RunFengYuan Business Center, Block 74, Baoan District, Shenzhen, China.

Postal code:518103

Tel: +86-755-2778 8210

FAX :+86-755-2346 2890

Web:www.sam-smt.com



Address: Rm B306, Build A, RunFengYuan Business Center, Block 74, Baoan District, Shenzhen, China.

Postal code: 518103

Tel: +86-755-2778 8210

FAX: +86-755-2346 2890

Web: www.sam-smt.com