

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1177	0.15	0.00	0.0%	3.65	3.65
0.10	1095	0.66	11.46	72.5%	4.35	15.81
0.20	1043	1.17	21.85	78.1%	6.12	27.97
0.30	992	1.67	31.16	77.6%	8.97	40.13
0.40	941	2.18	39.40	75.3%	12.89	52.29
0.50	889	2.69	46.56	72.2%	17.89	64.45
0.60	838	3.19	52.65	68.7%	23.97	76.61
0.70	787	3.70	57.66	65.0%	31.12	88.78
0.80	735	4.21	61.60	61.0%	39.34	100.94
0.90	684	4.71	64.46	57.0%	48.64	113.10
1.00	633	5.22	66.25	52.9%	59.01	125.26
1.10	581	5.73	66.96	48.7%	70.46	137.42
1.20	530	6.23	66.59	44.5%	82.99	149.58
1.30	479	6.74	65.16	40.3%	96.59	161.74
1.40	427	7.25	62.64	36.0%	111.26	173.90
1.50	376	7.75	59.05	31.7%	127.01	186.06
1.60	325	8.26	54.39	27.4%	143.83	198.22
1.70	273	8.77	48.65	23.1%	161.73	210.39
1.80	222	9.27	41.84	18.8%	180.71	222.55
1.90	171	9.78	33.95	14.5%	200.76	234.71
2.00	119	10.29	24.99	10.1%	221.88	246.87
2.10	68	10.79	14.95	5.8%	244.08	259.03
2.20	17	11.30	3.84	1.4%	267.35	271.19
2.30	-35	11.81	-8.35	-2.9%	291.70	283.35
2.40	-86	12.31	-21.62	-7.3%	317.13	295.51
2.50	-137	12.82	-35.96	-11.7%	343.63	307.67
2.60	-189	13.33	-51.37	-16.1%	371.20	319.83
2.70	-240	13.83	-67.86	-20.4%	399.85	332.00
2.80	-291	14.34	-85.42	-24.8%	429.58	344.16
2.90	-343	14.85	-104.06	-29.2%	460.38	356.32
3.00	-394	15.35	-123.77	-33.6%	492.25	368.48