

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2457	1.48	0.00	0.0%	17.73	17.73
0.10	2328	3.59	24.38	56.6%	18.69	43.07
0.20	2275	5.70	47.64	69.6%	20.76	68.41
0.30	2221	7.81	69.78	74.4%	23.96	93.74
0.40	2168	9.92	90.80	76.3%	28.28	119.08
0.50	2114	12.03	110.70	76.7%	33.71	144.41
0.60	2061	14.15	129.47	76.3%	40.27	169.75
0.70	2007	16.26	147.13	75.4%	47.96	195.08
0.80	1954	18.37	163.66	74.2%	56.76	220.42
0.90	1900	20.48	179.07	72.9%	66.68	245.75
1.00	1846	22.59	193.36	71.3%	77.73	271.09
1.10	1793	24.70	206.53	69.7%	89.90	296.42
1.20	1739	26.81	218.57	67.9%	103.19	321.76
1.30	1686	28.92	229.50	66.1%	117.60	347.10
1.40	1632	31.04	239.30	64.3%	133.13	372.43
1.50	1579	33.15	247.99	62.3%	149.78	397.77
1.60	1525	35.26	255.55	60.4%	167.55	423.10
1.70	1472	37.37	261.99	58.4%	186.45	448.44
1.80	1418	39.48	267.31	56.4%	206.47	473.77
1.90	1365	41.59	271.50	54.4%	227.60	499.11
2.00	1311	43.70	274.58	52.4%	249.86	524.44
2.10	1257	45.81	276.53	50.3%	273.25	549.78
2.20	1204	47.93	277.37	48.2%	297.75	575.11
2.30	1150	50.04	277.08	46.1%	323.37	600.45
2.40	1097	52.15	275.67	44.1%	350.12	625.78
2.50	1043	54.26	273.14	41.9%	377.98	651.12
2.60	990	56.37	269.48	39.8%	406.97	676.46
2.70	936	58.48	264.71	37.7%	437.08	701.79
2.80	883	60.59	258.81	35.6%	468.31	727.13
2.90	829	62.71	251.80	33.5%	500.66	752.46
3.00	776	64.82	243.66	31.3%	534.14	777.80