

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	4903	2.53	0.00	0.0%	60.81	60.81
0.10	4721	4.64	49.44	44.3%	62.04	111.48
0.20	4667	6.76	97.75	60.3%	64.39	162.15
0.30	4614	8.87	144.95	68.1%	67.87	212.82
0.40	4560	10.98	191.02	72.5%	72.47	263.49
0.50	4507	13.09	235.97	75.1%	78.19	314.16
0.60	4453	15.20	279.80	76.7%	85.03	364.83
0.70	4400	17.31	322.51	77.6%	92.99	415.50
0.80	4346	19.42	364.10	78.1%	102.07	466.17
0.90	4293	21.54	404.57	78.3%	112.28	516.84
1.00	4239	23.65	443.91	78.2%	123.60	567.51
1.10	4185	25.76	482.13	78.0%	136.05	618.18
1.20	4132	27.87	519.24	77.6%	149.62	668.86
1.30	4078	29.98	555.22	77.2%	164.31	719.53
1.40	4025	32.09	590.08	76.6%	180.12	770.20
1.50	3971	34.20	623.81	76.0%	197.05	820.87
1.60	3918	36.31	656.43	75.3%	215.11	871.54
1.70	3864	38.43	687.92	74.6%	234.29	922.21
1.80	3811	40.54	718.30	73.8%	254.58	972.88
1.90	3757	42.65	747.55	73.0%	276.00	1023.55
2.00	3704	44.76	775.68	72.2%	298.54	1074.22
2.10	3650	46.87	802.69	71.4%	322.20	1124.89
2.20	3597	48.98	828.58	70.5%	346.99	1175.56
2.30	3543	51.09	853.34	69.6%	372.89	1226.23
2.40	3489	53.20	876.99	68.7%	399.92	1276.91
2.50	3436	55.32	899.51	67.8%	428.06	1327.58
2.60	3382	57.43	920.92	66.8%	457.33	1378.25
2.70	3329	59.54	941.20	65.9%	487.72	1428.92
2.80	3275	61.65	960.36	64.9%	519.23	1479.59
2.90	3222	63.76	978.40	63.9%	551.86	1530.26
3.00	3168	65.87	995.31	63.0%	585.62	1580.93