

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	4209	2.17	0.00	0.0%	52.12	52.12
0.10	4035	3.98	42.25	44.2%	53.30	95.55
0.20	3983	5.79	83.43	60.0%	55.56	138.98
0.30	3932	7.60	123.53	67.7%	58.88	182.42
0.40	3881	9.41	162.56	72.0%	63.29	225.85
0.50	3830	11.22	200.51	74.5%	68.77	269.28
0.60	3778	13.03	237.40	75.9%	75.32	312.71
0.70	3727	14.84	273.20	76.7%	82.94	356.14
0.80	3676	16.65	307.94	77.1%	91.64	399.58
0.90	3624	18.46	341.59	77.1%	101.41	443.01
1.00	3573	20.27	374.18	76.9%	112.26	486.44
1.10	3522	22.08	405.69	76.6%	124.18	529.87
1.20	3471	23.89	436.13	76.1%	137.18	573.30
1.30	3419	25.70	465.49	75.5%	151.25	616.74
1.40	3368	27.51	493.78	74.8%	166.39	660.17
1.50	3317	29.32	521.00	74.0%	182.61	703.60
1.60	3265	31.13	547.14	73.2%	199.90	747.03
1.70	3214	32.94	572.20	72.4%	218.26	790.47
1.80	3163	34.75	596.20	71.5%	237.70	833.90
1.90	3112	36.56	619.12	70.6%	258.21	877.33
2.00	3060	38.37	640.96	69.6%	279.80	920.76
2.10	3009	40.17	661.73	68.6%	302.46	964.19
2.20	2958	41.98	681.43	67.6%	326.19	1007.63
2.30	2907	43.79	700.06	66.6%	351.00	1051.06
2.40	2855	45.60	717.61	65.6%	376.89	1094.49
2.50	2804	47.41	734.08	64.5%	403.84	1137.92
2.60	2753	49.22	749.48	63.4%	431.87	1181.35
2.70	2701	51.03	763.81	62.4%	460.98	1224.79
2.80	2650	52.84	777.06	61.3%	491.15	1268.22
2.90	2599	54.65	789.24	60.2%	522.41	1311.65
3.00	2548	56.46	800.35	59.1%	554.73	1355.08
0.72	3717	15.20	280.23	76.8%	84.60	364.83