

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1839	0.40	0.00	0.0%	9.50	9.50
0.10	1740	1.19	18.22	63.9%	10.28	28.50
0.20	1690	1.98	35.40	74.5%	12.11	47.50
0.30	1640	2.77	51.53	77.5%	14.98	66.51
0.40	1590	3.56	66.62	77.9%	18.89	85.51
0.50	1541	4.35	80.67	77.2%	23.84	104.51
0.60	1491	5.15	93.67	75.8%	29.84	123.51
0.70	1441	5.94	105.63	74.1%	36.88	142.51
0.80	1391	6.73	116.55	72.2%	44.97	161.51
0.90	1341	7.52	126.42	70.0%	54.09	180.51
1.00	1292	8.31	135.25	67.8%	64.26	199.52
1.10	1242	9.10	143.04	65.5%	75.48	218.52
1.20	1192	9.90	149.79	63.1%	87.73	237.52
1.30	1142	10.69	155.49	60.6%	101.03	256.52
1.40	1092	11.48	160.15	58.1%	115.37	275.52
1.50	1043	12.27	163.76	55.6%	130.76	294.52
1.60	993	13.06	166.34	53.1%	147.19	313.53
1.70	943	13.86	167.87	50.5%	164.66	332.53
1.80	893	14.65	168.35	47.9%	183.17	351.53
1.90	843	15.44	167.80	45.3%	202.73	370.53
2.00	794	16.23	166.20	42.7%	223.33	389.53
2.10	744	17.02	163.56	40.0%	244.98	408.53
2.20	694	17.81	159.87	37.4%	267.66	427.54
2.30	644	18.61	155.14	34.7%	291.39	446.54
2.40	594	19.40	149.37	32.1%	316.17	465.54
2.50	545	20.19	142.56	29.4%	341.98	484.54
2.60	495	20.98	134.70	26.8%	368.84	503.54
2.70	445	21.77	125.80	24.1%	396.75	522.54
2.80	395	22.56	115.85	21.4%	425.69	541.54
2.90	345	23.36	104.87	18.7%	455.68	560.55
3.00	296	24.15	92.83	16.0%	486.71	579.55