

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1731	0.37	0.00	0.0%	8.94	8.94
0.10	1637	1.12	17.15	63.9%	9.68	26.83
0.20	1591	1.86	33.31	74.5%	11.40	44.71
0.30	1544	2.61	48.50	77.5%	14.10	62.59
0.40	1497	3.35	62.70	77.9%	17.78	80.48
0.50	1450	4.10	75.92	77.2%	22.44	98.36
0.60	1403	4.84	88.16	75.8%	28.09	116.24
0.70	1356	5.59	99.42	74.1%	34.71	134.13
0.80	1309	6.33	109.69	72.2%	42.32	152.01
0.90	1262	7.08	118.99	70.0%	50.91	169.90
1.00	1216	7.82	127.30	67.8%	60.48	187.78
1.10	1169	8.57	134.63	65.5%	71.04	205.66
1.20	1122	9.31	140.98	63.1%	82.57	223.55
1.30	1075	10.06	146.34	60.6%	95.09	241.43
1.40	1028	10.80	150.73	58.1%	108.59	259.32
1.50	981	11.55	154.13	55.6%	123.07	277.20
1.60	934	12.30	156.55	53.1%	138.53	295.08
1.70	887	13.04	157.99	50.5%	154.97	312.97
1.80	841	13.79	158.45	47.9%	172.40	330.85
1.90	794	14.53	157.93	45.3%	190.81	348.73
2.00	747	15.28	156.42	42.7%	210.20	366.62
2.10	700	16.02	153.94	40.0%	230.57	384.50
2.20	653	16.77	150.47	37.4%	251.92	402.39
2.30	606	17.51	146.02	34.7%	274.25	420.27
2.40	559	18.26	140.58	32.1%	297.57	438.15
2.50	512	19.00	134.17	29.4%	321.87	456.04
2.60	466	19.75	126.77	26.8%	347.15	473.92
2.70	419	20.49	118.40	24.1%	373.41	491.81
2.80	372	21.24	109.04	21.4%	400.65	509.69
2.90	325	21.98	98.70	18.7%	428.88	527.57
3.00	278	22.73	87.37	16.0%	458.08	545.46