

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1638	0.35	0.00	0.0%	8.45	8.45
0.10	1538	1.06	16.11	63.6%	9.23	25.34
0.20	1489	1.76	31.18	73.8%	11.05	42.23
0.30	1439	2.46	45.21	76.5%	13.90	59.12
0.40	1389	3.17	58.20	76.6%	17.80	76.01
0.50	1340	3.87	70.15	75.5%	22.74	92.90
0.60	1290	4.57	81.06	73.8%	28.72	109.79
0.70	1240	5.28	90.93	71.8%	35.74	126.68
0.80	1191	5.98	99.76	69.5%	43.80	143.57
0.90	1141	6.69	107.55	67.0%	52.90	160.46
1.00	1092	7.39	114.31	64.5%	63.04	177.35
1.10	1042	8.09	120.02	61.8%	74.22	194.24
1.20	992	8.80	124.69	59.1%	86.44	211.13
1.30	943	9.50	128.32	56.3%	99.70	228.02
1.40	893	10.20	130.91	53.5%	114.00	244.91
1.50	843	10.91	132.46	50.6%	129.34	261.80
1.60	794	11.61	132.97	47.7%	145.72	278.69
1.70	744	12.32	132.44	44.8%	163.14	295.58
1.80	694	13.02	130.87	41.9%	181.60	312.47
1.90	645	13.72	128.26	38.9%	201.10	329.36
2.00	595	14.43	124.62	36.0%	221.64	346.25
2.10	545	15.13	119.93	33.0%	243.21	363.14
2.20	496	15.83	114.20	30.0%	265.83	380.03
2.30	446	16.54	107.43	27.1%	289.49	396.92
2.40	396	17.24	99.62	24.1%	314.19	413.81
2.50	347	17.95	90.77	21.1%	339.93	430.70
2.60	297	18.65	80.88	18.1%	366.71	447.59
2.70	247	19.35	69.95	15.1%	394.53	464.48
2.80	198	20.06	57.99	12.0%	423.39	481.37
2.90	148	20.76	44.98	9.0%	453.29	498.26
3.00	98	21.46	30.93	6.0%	484.22	515.15