

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2452	0.25	0.00	0.0%	15.20	15.20
0.10	2334	0.68	24.44	60.3%	16.10	40.54
0.20	2280	1.10	47.75	72.5%	18.12	65.87
0.30	2226	1.52	69.94	76.7%	21.26	91.21
0.40	2173	1.94	91.01	78.1%	25.53	116.54
0.50	2119	2.36	110.96	78.2%	30.92	141.88
0.60	2066	2.79	129.78	77.6%	37.43	167.21
0.70	2012	3.21	147.49	76.6%	45.06	192.55
0.80	1958	3.63	164.06	75.3%	53.82	217.88
0.90	1905	4.05	179.52	73.8%	63.70	243.22
1.00	1851	4.48	193.85	72.2%	74.70	268.56
1.10	1798	4.90	207.06	70.5%	86.83	293.89
1.20	1744	5.32	219.15	68.7%	100.07	319.23
1.30	1690	5.74	230.12	66.8%	114.44	344.56
1.40	1637	6.16	239.96	64.9%	129.94	369.90
1.50	1583	6.59	248.68	62.9%	146.55	395.23
1.60	1530	7.01	256.28	60.9%	164.29	420.57
1.70	1476	7.43	262.75	58.9%	183.15	445.90
1.80	1422	7.85	268.11	56.9%	203.13	471.24
1.90	1369	8.28	272.34	54.8%	224.24	496.57
2.00	1315	8.70	275.44	52.8%	246.47	521.91
2.10	1262	9.12	277.43	50.7%	269.82	547.25
2.20	1208	9.54	278.29	48.6%	294.29	572.58
2.30	1154	9.97	278.03	46.5%	319.89	597.92
2.40	1101	10.39	276.64	44.4%	346.61	623.25
2.50	1047	10.81	274.14	42.3%	374.45	648.59
2.60	994	11.23	270.51	40.1%	403.41	673.92
2.70	940	11.65	265.76	38.0%	433.50	699.26
2.80	886	12.08	259.88	35.9%	464.71	724.59
2.90	833	12.50	252.89	33.7%	497.04	749.93
3.00	779	12.92	244.77	31.6%	530.50	775.26