

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1845	0.95	0.00	0.0%	11.40	11.40
0.10	1734	2.53	18.16	59.7%	12.24	30.40
0.20	1684	4.12	35.27	71.4%	14.14	49.40
0.30	1634	5.70	51.32	75.0%	17.08	68.41
0.40	1583	7.28	66.32	75.9%	21.08	87.41
0.50	1533	8.87	80.27	75.4%	26.14	106.41
0.60	1483	10.45	93.17	74.3%	32.24	125.41
0.70	1433	12.03	105.01	72.7%	39.40	144.41
0.80	1382	13.62	115.81	70.9%	47.61	163.41
0.90	1332	15.20	125.55	68.8%	56.87	182.42
1.00	1282	16.78	134.23	66.6%	67.18	201.42
1.10	1232	18.37	141.87	64.4%	78.55	220.42
1.20	1181	19.95	148.45	62.0%	90.97	239.42
1.30	1131	21.54	153.98	59.6%	104.44	258.42
1.40	1081	23.12	158.46	57.1%	118.96	277.42
1.50	1031	24.70	161.88	54.6%	134.54	296.42
1.60	980	26.29	164.26	52.1%	151.17	315.43
1.70	930	27.87	165.58	49.5%	168.85	334.43
1.80	880	29.45	165.84	46.9%	187.59	353.43
1.90	830	31.04	165.06	44.3%	207.37	372.43
2.00	779	32.62	163.22	41.7%	228.21	391.43
2.10	729	34.20	160.33	39.1%	250.10	410.43
2.20	679	35.79	156.39	36.4%	273.05	429.44
2.30	629	37.37	151.39	33.8%	297.05	448.44
2.40	578	38.95	145.34	31.1%	322.09	467.44
2.50	528	40.54	138.24	28.4%	348.20	486.44
2.60	478	42.12	130.09	25.7%	375.35	505.44
2.70	428	43.70	120.89	23.1%	403.56	524.44
2.80	377	45.29	110.63	20.4%	432.82	543.44
2.90	327	46.87	99.32	17.7%	463.13	562.45
3.00	277	48.45	86.96	15.0%	494.49	581.45