

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	3684	1.74	0.00	0.0%	41.80	41.80
0.10	3524	3.33	36.90	46.2%	42.91	79.81
0.20	3473	4.91	72.74	61.7%	45.07	117.81
0.30	3423	6.49	107.54	69.0%	48.28	155.81
0.40	3373	8.08	141.28	72.9%	52.54	193.82
0.50	3322	9.66	173.97	75.0%	57.85	231.82
0.60	3272	11.24	205.60	76.2%	64.22	269.82
0.70	3222	12.83	236.18	76.7%	71.64	307.83
0.80	3172	14.41	265.71	76.8%	80.11	345.83
0.90	3121	15.99	294.19	76.6%	89.64	383.83
1.00	3071	17.58	321.62	76.2%	100.22	421.83
1.10	3021	19.16	347.99	75.7%	111.85	459.84
1.20	2971	20.74	373.31	75.0%	124.53	497.84
1.30	2920	22.33	397.58	74.2%	138.26	535.84
1.40	2870	23.91	420.80	73.3%	153.05	573.85
1.50	2820	25.49	442.96	72.4%	168.89	611.85
1.60	2770	27.08	464.07	71.4%	185.78	649.85
1.70	2719	28.66	484.13	70.4%	203.73	687.86
1.80	2669	30.24	503.13	69.3%	222.73	725.86
1.90	2619	31.83	521.09	68.2%	242.78	763.86
2.00	2569	33.41	537.99	67.1%	263.88	801.87
2.10	2518	34.99	553.84	65.9%	286.03	839.87
2.20	2468	36.58	568.63	64.8%	309.24	877.87
2.30	2418	38.16	582.38	63.6%	333.50	915.88
2.40	2368	39.74	595.07	62.4%	358.81	953.88
2.50	2317	41.33	606.71	61.2%	385.18	991.88
2.60	2267	42.91	617.29	59.9%	412.59	1029.89
2.70	2217	44.50	626.82	58.7%	441.06	1067.89
2.80	2167	46.08	635.31	57.4%	470.59	1105.89
2.90	2116	47.66	642.73	56.2%	501.16	1143.89
3.00	2066	49.25	649.11	54.9%	532.79	1181.90
0.28	3433	6.18	100.66	67.9%	47.55	148.21