

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2680	0.92	0.00	0.0%	22.11	22.11
0.10	2548	2.07	26.69	53.6%	23.06	49.75
0.20	2498	3.22	52.31	67.6%	25.08	77.39
0.30	2447	4.38	76.88	73.2%	28.15	105.03
0.40	2397	5.53	100.39	75.7%	32.28	132.67
0.50	2346	6.68	122.83	76.6%	37.47	160.30
0.60	2295	7.83	144.22	76.7%	43.72	187.94
0.70	2245	8.98	164.55	76.3%	51.03	215.58
0.80	2194	10.13	183.82	75.6%	59.40	243.22
0.90	2144	11.29	202.03	74.6%	68.83	270.86
1.00	2093	12.44	219.18	73.4%	79.31	298.50
1.10	2042	13.59	235.28	72.1%	90.86	326.14
1.20	1992	14.74	250.31	70.8%	103.47	353.77
1.30	1941	15.89	264.28	69.3%	117.13	381.41
1.40	1891	17.04	277.20	67.8%	131.86	409.05
1.50	1840	18.20	289.05	66.2%	147.64	436.69
1.60	1790	19.35	299.85	64.6%	164.48	464.33
1.70	1739	20.50	309.58	62.9%	182.39	491.97
1.80	1688	21.65	318.26	61.2%	201.35	519.61
1.90	1638	22.80	325.88	59.5%	221.37	547.25
2.00	1587	23.95	332.43	57.8%	242.45	574.88
2.10	1537	25.11	337.93	56.1%	264.59	602.52
2.20	1486	26.26	342.37	54.3%	287.79	630.16
2.30	1436	27.41	345.75	52.6%	312.05	657.80
2.40	1385	28.56	348.07	50.8%	337.36	685.44
2.50	1334	29.71	349.34	49.0%	363.74	713.08
2.60	1284	30.86	349.54	47.2%	391.18	740.72
2.70	1233	32.01	348.68	45.4%	419.67	768.35
2.80	1183	33.17	346.76	43.6%	449.23	795.99
2.90	1132	34.32	343.79	41.7%	479.84	823.63
3.00	1081	35.47	339.75	39.9%	511.52	851.27