

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2267	0.68	0.00	0.0%	16.37	16.37
0.10	2151	1.66	22.53	56.7%	17.23	39.76
0.20	2103	2.63	44.04	69.7%	19.10	63.14
0.30	2054	3.61	64.54	74.6%	21.99	86.53
0.40	2006	4.58	84.03	76.5%	25.88	109.92
0.50	1958	5.55	102.51	76.9%	30.79	133.30
0.60	1910	6.53	119.98	76.6%	36.71	156.69
0.70	1861	7.50	136.43	75.8%	43.64	180.08
0.80	1813	8.48	151.87	74.6%	51.59	203.46
0.90	1765	9.45	166.30	73.3%	60.54	226.85
1.00	1716	10.43	179.72	71.8%	70.51	250.24
1.10	1668	11.40	192.13	70.2%	81.49	273.62
1.20	1620	12.38	203.52	68.5%	93.49	297.01
1.30	1571	13.35	213.91	66.8%	106.49	320.40
1.40	1523	14.32	223.28	64.9%	120.51	343.78
1.50	1475	15.30	231.63	63.1%	135.53	367.17
1.60	1426	16.27	238.98	61.2%	151.57	390.56
1.70	1378	17.25	245.32	59.3%	168.63	413.94
1.80	1330	18.22	250.64	57.3%	186.69	437.33
1.90	1281	19.20	254.95	55.3%	205.77	460.71
2.00	1233	20.17	258.25	53.3%	225.86	484.10
2.10	1185	21.15	260.53	51.3%	246.96	507.49
2.20	1136	22.12	261.81	49.3%	269.07	530.87
2.30	1088	23.09	262.07	47.3%	292.19	554.26
2.40	1040	24.07	261.32	45.2%	316.33	577.65
2.50	991	25.04	259.56	43.2%	341.48	601.03
2.60	943	26.02	256.78	41.1%	367.64	624.42
2.70	895	26.99	253.00	39.1%	394.81	647.81
2.80	846	27.97	248.20	37.0%	422.99	671.19
2.90	798	28.94	242.39	34.9%	452.19	694.58
3.00	750	29.92	235.57	32.8%	482.40	717.97