

| T (n.m) | N (r.p.m.) | I (amps) | Pout(w) | Eff.(%) | Loss(w) | Pin(w) |
|----------------|-------------------|-----------------|----------------|----------------|----------------|---------------|
| 0.00 | 2105 | 0.63 | 0.00 | 0.0% | 15.20 | 15.20 |
| 0.10 | 1997 | 1.54 | 20.92 | 56.7% | 16.00 | 36.92 |
| 0.20 | 1953 | 2.44 | 40.89 | 69.7% | 17.74 | 58.63 |
| 0.30 | 1908 | 3.35 | 59.93 | 74.6% | 20.42 | 80.35 |
| 0.40 | 1863 | 4.25 | 78.03 | 76.5% | 24.03 | 102.07 |
| 0.50 | 1818 | 5.16 | 95.19 | 76.9% | 28.59 | 123.78 |
| 0.60 | 1773 | 6.06 | 111.41 | 76.6% | 34.09 | 145.50 |
| 0.70 | 1728 | 6.97 | 126.69 | 75.8% | 40.53 | 167.21 |
| 0.80 | 1683 | 7.87 | 141.03 | 74.6% | 47.90 | 188.93 |
| 0.90 | 1639 | 8.78 | 154.43 | 73.3% | 56.22 | 210.65 |
| 1.00 | 1594 | 9.68 | 166.89 | 71.8% | 65.48 | 232.36 |
| 1.10 | 1549 | 10.59 | 178.41 | 70.2% | 75.67 | 254.08 |
| 1.20 | 1504 | 11.49 | 188.99 | 68.5% | 86.81 | 275.79 |
| 1.30 | 1459 | 12.40 | 198.63 | 66.8% | 98.88 | 297.51 |
| 1.40 | 1414 | 13.30 | 207.33 | 64.9% | 111.90 | 319.23 |
| 1.50 | 1369 | 14.21 | 215.09 | 63.1% | 125.85 | 340.94 |
| 1.60 | 1324 | 15.11 | 221.91 | 61.2% | 140.75 | 362.66 |
| 1.70 | 1280 | 16.02 | 227.79 | 59.3% | 156.58 | 384.37 |
| 1.80 | 1235 | 16.92 | 232.73 | 57.3% | 173.36 | 406.09 |
| 1.90 | 1190 | 17.83 | 236.74 | 55.3% | 191.07 | 427.81 |
| 2.00 | 1145 | 18.73 | 239.80 | 53.3% | 209.72 | 449.52 |
| 2.10 | 1100 | 19.63 | 241.92 | 51.3% | 229.32 | 471.24 |
| 2.20 | 1055 | 20.54 | 243.11 | 49.3% | 249.85 | 492.95 |
| 2.30 | 1010 | 21.44 | 243.35 | 47.3% | 271.32 | 514.67 |
| 2.40 | 965 | 22.35 | 242.65 | 45.2% | 293.73 | 536.39 |
| 2.50 | 921 | 23.25 | 241.02 | 43.2% | 317.09 | 558.10 |
| 2.60 | 876 | 24.16 | 238.44 | 41.1% | 341.38 | 579.82 |
| 2.70 | 831 | 25.06 | 234.93 | 39.1% | 366.61 | 601.54 |
| 2.80 | 786 | 25.97 | 230.47 | 37.0% | 392.78 | 623.25 |
| 2.90 | 741 | 26.87 | 225.08 | 34.9% | 419.89 | 644.97 |
| 3.00 | 696 | 27.78 | 218.74 | 32.8% | 447.94 | 666.68 |