

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2760	0.12	0.00	0.0%	21.38	21.38
0.10	2633	0.28	27.57	55.3%	22.31	49.88
0.20	2582	0.44	54.07	69.0%	24.31	78.38
0.30	2531	0.59	79.51	74.4%	27.38	106.88
0.40	2480	0.75	103.88	76.7%	31.51	135.39
0.50	2429	0.91	127.18	77.6%	36.71	163.89
0.60	2378	1.07	149.42	77.7%	42.98	192.39
0.70	2327	1.23	170.59	77.2%	50.31	220.89
0.80	2276	1.39	190.69	76.5%	58.71	249.40
0.90	2225	1.54	209.72	75.5%	68.17	277.90
1.00	2174	1.70	227.69	74.3%	78.71	306.40
1.10	2123	1.86	244.60	73.0%	90.30	334.90
1.20	2072	2.02	260.43	71.7%	102.97	363.40
1.30	2022	2.18	275.21	70.2%	116.70	391.91
1.40	1971	2.34	288.91	68.7%	131.50	420.41
1.50	1920	2.49	301.55	67.2%	147.37	448.91
1.60	1869	2.65	313.12	65.6%	164.30	477.41
1.70	1818	2.81	323.62	64.0%	182.30	505.92
1.80	1767	2.97	333.06	62.3%	201.36	534.42
1.90	1716	3.13	341.43	60.7%	221.49	562.92
2.00	1665	3.29	348.73	59.0%	242.69	591.42
2.10	1614	3.44	354.97	57.3%	264.96	619.93
2.20	1563	3.60	360.14	55.5%	288.29	648.43
2.30	1512	3.76	364.24	53.8%	312.69	676.93
2.40	1461	3.92	367.28	52.1%	338.15	705.43
2.50	1410	4.08	369.25	50.3%	364.68	733.94
2.60	1360	4.24	370.16	48.5%	392.28	762.44
2.70	1309	4.39	370.00	46.8%	420.94	790.94
2.80	1258	4.55	368.77	45.0%	450.68	819.44
2.90	1207	4.71	366.47	43.2%	481.47	847.94
3.00	1156	4.87	363.11	41.4%	513.34	876.45