

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2303	0.10	0.00	0.0%	17.81	17.81
0.10	2186	0.23	22.89	55.1%	18.67	41.57
0.20	2139	0.36	44.81	68.6%	20.51	65.32
0.30	2092	0.49	65.74	73.8%	23.33	89.07
0.40	2046	0.63	85.69	75.9%	27.14	112.82
0.50	1999	0.76	104.65	76.6%	31.92	136.57
0.60	1952	0.89	122.64	76.5%	37.68	160.33
0.70	1905	1.02	139.65	75.9%	44.43	184.08
0.80	1858	1.15	155.67	74.9%	52.16	207.83
0.90	1811	1.29	170.72	73.7%	60.87	231.58
1.00	1765	1.42	184.78	72.4%	70.55	255.33
1.10	1718	1.55	197.86	70.9%	81.23	279.09
1.20	1671	1.68	209.96	69.3%	92.88	302.84
1.30	1624	1.81	221.08	67.7%	105.51	326.59
1.40	1577	1.95	231.22	66.0%	119.13	350.34
1.50	1530	2.08	240.37	64.3%	133.72	374.09
1.60	1483	2.21	248.55	62.5%	149.30	397.85
1.70	1437	2.34	255.74	60.7%	165.86	421.60
1.80	1390	2.47	261.95	58.8%	183.40	445.35
1.90	1343	2.61	267.19	57.0%	201.92	469.10
2.00	1296	2.74	271.44	55.1%	221.42	492.85
2.10	1249	2.87	274.70	53.2%	241.90	516.61
2.20	1202	3.00	276.99	51.3%	263.36	540.36
2.30	1155	3.13	278.30	49.3%	285.81	564.11
2.40	1109	3.27	278.62	47.4%	309.24	587.86
2.50	1062	3.40	277.97	45.4%	333.64	611.61
2.60	1015	3.53	276.33	43.5%	359.03	635.36
2.70	968	3.66	273.71	41.5%	385.40	659.12
2.80	921	3.79	270.11	39.6%	412.76	682.87
2.90	874	3.93	265.53	37.6%	441.09	706.62
3.00	828	4.06	259.97	35.6%	470.40	730.37