

| T (n.m) | N (r.p.m.) | I (amps) | Pout(w) | Eff.(%) | Loss(w) | Pin(w) |
|----------------|-------------------|-----------------|----------------|----------------|----------------|---------------|
| 0.00 | 2948 | 1.14 | 0.00 | 0.0% | 27.36 | 27.36 |
| 0.10 | 2809 | 2.41 | 29.41 | 50.9% | 28.35 | 57.76 |
| 0.20 | 2759 | 3.67 | 57.79 | 65.5% | 30.38 | 88.17 |
| 0.30 | 2709 | 4.94 | 85.12 | 71.8% | 33.45 | 118.57 |
| 0.40 | 2660 | 6.21 | 111.41 | 74.8% | 37.57 | 148.97 |
| 0.50 | 2610 | 7.47 | 136.65 | 76.2% | 42.72 | 179.37 |
| 0.60 | 2560 | 8.74 | 160.86 | 76.7% | 48.92 | 209.78 |
| 0.70 | 2510 | 10.01 | 184.03 | 76.6% | 56.15 | 240.18 |
| 0.80 | 2461 | 11.27 | 206.15 | 76.2% | 64.43 | 270.58 |
| 0.90 | 2411 | 12.54 | 227.24 | 75.5% | 73.75 | 300.98 |
| 1.00 | 2361 | 13.81 | 247.28 | 74.6% | 84.11 | 331.39 |
| 1.10 | 2312 | 15.07 | 266.28 | 73.6% | 95.51 | 361.79 |
| 1.20 | 2262 | 16.34 | 284.24 | 72.5% | 107.95 | 392.19 |
| 1.30 | 2212 | 17.61 | 301.16 | 71.3% | 121.44 | 422.59 |
| 1.40 | 2162 | 18.87 | 317.04 | 70.0% | 135.96 | 453.00 |
| 1.50 | 2113 | 20.14 | 331.87 | 68.7% | 151.53 | 483.40 |
| 1.60 | 2063 | 21.41 | 345.67 | 67.3% | 168.13 | 513.80 |
| 1.70 | 2013 | 22.68 | 358.42 | 65.9% | 185.78 | 544.20 |
| 1.80 | 1964 | 23.94 | 370.14 | 64.4% | 204.47 | 574.61 |
| 1.90 | 1914 | 25.21 | 380.81 | 62.9% | 224.20 | 605.01 |
| 2.00 | 1864 | 26.48 | 390.44 | 61.4% | 244.97 | 635.41 |
| 2.10 | 1814 | 27.74 | 399.03 | 59.9% | 266.79 | 665.81 |
| 2.20 | 1765 | 29.01 | 406.58 | 58.4% | 289.64 | 696.22 |
| 2.30 | 1715 | 30.28 | 413.08 | 56.8% | 313.54 | 726.62 |
| 2.40 | 1665 | 31.54 | 418.55 | 55.3% | 338.48 | 757.02 |
| 2.50 | 1616 | 32.81 | 422.97 | 53.7% | 364.45 | 787.42 |
| 2.60 | 1566 | 34.08 | 426.36 | 52.1% | 391.47 | 817.83 |
| 2.70 | 1516 | 35.34 | 428.70 | 50.5% | 419.53 | 848.23 |
| 2.80 | 1466 | 36.61 | 430.00 | 48.9% | 448.63 | 878.63 |
| 2.90 | 1417 | 37.88 | 430.26 | 47.3% | 478.78 | 909.04 |
| 3.00 | 1367 | 39.14 | 429.48 | 45.7% | 509.96 | 939.44 |