

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	3683	3.17	0.00	0.0%	38.00	38.00
0.10	3520	6.33	36.86	48.5%	39.14	76.01
0.20	3466	9.50	72.59	63.7%	41.42	114.01
0.30	3411	12.67	107.17	70.5%	44.84	152.01
0.40	3357	15.83	140.61	74.0%	49.41	190.02
0.50	3302	19.00	172.91	75.8%	55.11	228.02
0.60	3248	22.17	204.07	76.7%	61.95	266.02
0.70	3194	25.34	234.10	77.0%	69.93	304.03
0.80	3139	28.50	262.98	76.9%	79.05	342.03
0.90	3085	31.67	290.72	76.5%	89.31	380.03
1.00	3030	34.84	317.32	75.9%	100.71	418.03
1.10	2976	38.00	342.78	75.2%	113.26	456.04
1.20	2921	41.17	367.10	74.3%	126.94	494.04
1.30	2867	44.34	390.28	73.4%	141.76	532.04
1.40	2812	47.50	412.32	72.3%	157.72	570.05
1.50	2758	50.67	433.22	71.2%	174.83	608.05
1.60	2704	53.84	452.98	70.1%	193.07	646.05
1.70	2649	57.00	471.60	68.9%	212.45	684.06
1.80	2595	60.17	489.08	67.7%	232.98	722.06
1.90	2540	63.34	505.42	66.5%	254.64	760.06
2.00	2486	66.51	520.62	65.2%	277.44	798.07
2.10	2431	69.67	534.68	64.0%	301.39	836.07
2.20	2377	72.84	547.60	62.6%	326.47	874.07
2.30	2322	76.01	559.38	61.3%	352.70	912.08
2.40	2268	79.17	570.02	60.0%	380.06	950.08
2.50	2214	82.34	579.52	58.7%	408.57	988.08
2.60	2159	85.51	587.87	57.3%	438.21	1026.08
2.70	2105	88.67	595.09	55.9%	469.00	1064.09
2.80	2050	91.84	601.17	54.5%	500.92	1102.09
2.90	1996	95.01	606.11	53.2%	533.99	1140.09
3.00	1941	98.17	609.91	51.8%	568.19	1178.10