

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	2953	2.53	0.00	0.0%	30.40	30.40
0.10	2804	5.07	29.36	48.3%	31.44	60.81
0.20	2754	7.60	57.68	63.2%	33.53	91.21
0.30	2704	10.13	84.96	69.9%	36.65	121.61
0.40	2655	12.67	111.20	73.2%	40.81	152.01
0.50	2605	15.20	136.39	74.8%	46.02	182.42
0.60	2555	17.73	160.55	75.4%	52.27	212.82
0.70	2506	20.27	183.66	75.5%	59.56	243.22
0.80	2456	22.80	205.74	75.2%	67.89	273.62
0.90	2406	25.34	226.77	74.6%	77.26	304.03
1.00	2356	27.87	246.76	73.8%	87.67	334.43
1.10	2307	30.40	265.71	72.8%	99.12	364.83
1.20	2257	32.94	283.62	71.8%	111.62	395.23
1.30	2207	35.47	300.48	70.6%	125.15	425.64
1.40	2158	38.00	316.31	69.4%	139.73	456.04
1.50	2108	40.54	331.09	68.1%	155.35	486.44
1.60	2058	43.07	344.84	66.7%	172.01	516.84
1.70	2008	45.60	357.54	65.3%	189.71	547.25
1.80	1959	48.14	369.20	63.9%	208.45	577.65
1.90	1909	50.67	379.82	62.5%	228.23	608.05
2.00	1859	53.20	389.40	61.0%	249.06	638.45
2.10	1810	55.74	397.93	59.5%	270.92	668.86
2.20	1760	58.27	405.43	58.0%	293.83	699.26
2.30	1710	60.81	411.88	56.4%	317.78	729.66
2.40	1660	63.34	417.30	54.9%	342.76	760.06
2.50	1611	65.87	421.67	53.3%	368.79	790.47
2.60	1561	68.41	425.00	51.8%	395.87	820.87
2.70	1511	70.94	427.29	50.2%	423.98	851.27
2.80	1462	73.47	428.54	48.6%	453.13	881.67
2.90	1412	76.01	428.75	47.0%	483.33	912.08
3.00	1362	78.54	427.91	45.4%	514.56	942.48