

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2325	0.47	0.00	0.0%	16.80	16.80
0.10	2212	1.13	23.16	56.8%	17.64	40.80
0.20	2165	1.80	45.34	70.0%	19.46	64.81
0.30	2118	2.47	66.54	74.9%	22.27	88.81
0.40	2071	3.13	86.75	76.9%	26.06	112.81
0.50	2024	3.80	105.97	77.5%	30.84	136.81
0.60	1977	4.47	124.21	77.2%	36.60	160.81
0.70	1930	5.13	141.46	76.5%	43.35	184.82
0.80	1883	5.80	157.73	75.5%	51.09	208.82
0.90	1836	6.47	173.01	74.3%	59.81	232.82
1.00	1789	7.13	187.31	72.9%	69.51	256.82
1.10	1742	7.80	200.62	71.4%	80.20	280.82
1.20	1695	8.47	212.95	69.9%	91.88	304.83
1.30	1648	9.13	224.29	68.2%	104.54	328.83
1.40	1601	9.80	234.65	66.5%	118.18	352.83
1.50	1553	10.47	244.02	64.8%	132.81	376.83
1.60	1506	11.13	252.41	63.0%	148.43	400.83
1.70	1459	11.80	259.81	61.2%	165.03	424.84
1.80	1412	12.47	266.22	59.3%	182.61	448.84
1.90	1365	13.13	271.65	57.5%	201.19	472.84
2.00	1318	13.80	276.10	55.6%	220.74	496.84
2.10	1271	14.47	279.56	53.7%	241.28	520.84
2.20	1224	15.13	282.03	51.8%	262.81	544.84
2.30	1177	15.80	283.52	49.8%	285.32	568.85
2.40	1130	16.47	284.03	47.9%	308.82	592.85
2.50	1083	17.13	283.55	46.0%	333.30	616.85
2.60	1036	17.80	282.08	44.0%	358.77	640.85
2.70	989	18.47	279.63	42.1%	385.22	664.85
2.80	942	19.13	276.19	40.1%	412.66	688.86
2.90	895	19.80	271.77	38.1%	441.09	712.86
3.00	848	20.47	266.37	36.1%	470.50	736.86