

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1965	0.23	0.00	0.0%	11.15	11.15
0.10	1852	0.65	19.40	61.7%	12.02	31.42
0.20	1799	1.08	37.67	72.9%	14.01	51.68
0.30	1745	1.50	54.83	76.2%	17.13	71.95
0.40	1692	1.92	70.86	76.8%	21.36	92.22
0.50	1638	2.34	85.76	76.2%	26.72	112.49
0.60	1584	2.77	99.55	75.0%	33.21	132.76
0.70	1531	3.19	112.21	73.3%	40.81	153.03
0.80	1477	3.61	123.75	71.4%	49.54	173.29
0.90	1424	4.03	134.17	69.3%	59.39	193.56
1.00	1370	4.45	143.46	67.1%	70.37	213.83
1.10	1316	4.88	151.64	64.8%	82.46	234.10
1.20	1263	5.30	158.68	62.4%	95.68	254.37
1.30	1209	5.72	164.61	59.9%	110.02	274.64
1.40	1156	6.14	169.41	57.4%	125.49	294.90
1.50	1102	6.57	173.10	54.9%	142.08	315.17
1.60	1048	6.99	175.65	52.4%	159.79	335.44
1.70	995	7.41	177.09	49.8%	178.62	355.71
1.80	941	7.83	177.40	47.2%	198.57	375.98
1.90	888	8.26	176.59	44.6%	219.65	396.25
2.00	834	8.68	174.66	41.9%	241.85	416.51
2.10	780	9.10	171.61	39.3%	265.18	436.78
2.20	727	9.52	167.43	36.6%	289.62	457.05
2.30	673	9.94	162.13	34.0%	315.19	477.32
2.40	620	10.37	155.71	31.3%	341.88	497.59
2.50	566	10.79	148.16	28.6%	369.69	517.86
2.60	512	11.21	139.49	25.9%	398.63	538.12
2.70	459	11.63	129.70	23.2%	428.69	558.39
2.80	405	12.06	118.79	20.5%	459.87	578.66
2.90	352	12.48	106.75	17.8%	492.17	598.93
3.00	298	12.90	93.60	15.1%	525.60	619.20