

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	4252	0.42	0.00	0.0%	17.73	17.73
0.10	4169	1.48	43.66	70.3%	18.41	62.07
0.20	4123	2.53	86.34	81.1%	20.07	106.41
0.30	4076	3.59	128.06	85.0%	22.69	150.75
0.40	4030	4.64	168.80	86.5%	26.28	195.08
0.50	3984	5.70	208.58	87.1%	30.84	239.42
0.60	3937	6.76	247.38	87.2%	36.38	283.76
0.70	3891	7.81	285.21	86.9%	42.88	328.09
0.80	3844	8.87	322.07	86.5%	50.36	372.43
0.90	3798	9.92	357.96	85.9%	58.81	416.77
1.00	3752	10.98	392.88	85.2%	68.23	461.10
1.10	3705	12.03	426.82	84.4%	78.62	505.44
1.20	3659	13.09	459.80	83.6%	89.98	549.78
1.30	3613	14.15	491.80	82.8%	102.31	594.12
1.40	3566	15.20	522.84	81.9%	115.62	638.45
1.50	3520	16.26	552.90	81.0%	129.89	682.79
1.60	3474	17.31	581.99	80.0%	145.14	727.13
1.70	3427	18.37	610.11	79.1%	161.35	771.46
1.80	3381	19.42	637.26	78.1%	178.54	815.80
1.90	3334	20.48	663.44	77.1%	196.70	860.14
2.00	3288	21.54	688.65	76.1%	215.83	904.47
2.10	3242	22.59	712.88	75.1%	235.93	948.81
2.20	3195	23.65	736.15	74.1%	257.00	993.15
2.30	3149	24.70	758.44	73.1%	279.04	1037.49
2.40	3103	25.76	779.77	72.1%	302.06	1081.82
2.50	3056	26.81	800.12	71.0%	326.04	1126.16
2.60	3010	27.87	819.50	70.0%	351.00	1170.50
2.70	2964	28.92	837.91	69.0%	376.92	1214.83
2.80	2917	29.98	855.35	67.9%	403.82	1259.17
2.90	2871	31.04	871.82	66.9%	431.69	1303.51
3.00	2824	32.09	887.31	65.8%	460.53	1347.84