

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2208	0.38	0.00	0.0%	13.68	13.68
0.10	2096	1.01	21.95	60.2%	14.53	36.48
0.20	2046	1.65	42.85	72.3%	16.44	59.28
0.30	1995	2.28	62.68	76.4%	19.41	82.09
0.40	1945	2.91	81.46	77.7%	23.43	104.89
0.50	1894	3.55	99.17	77.7%	28.52	127.69
0.60	1843	4.18	115.82	77.0%	34.67	150.49
0.70	1793	4.81	131.42	75.8%	41.88	173.29
0.80	1742	5.45	145.95	74.4%	50.15	196.10
0.90	1692	6.08	159.42	72.8%	59.47	218.90
1.00	1641	6.71	171.84	71.1%	69.86	241.70
1.10	1590	7.35	183.19	69.3%	81.31	264.50
1.20	1540	7.98	193.49	67.3%	93.82	287.30
1.30	1489	8.61	202.72	65.4%	107.39	310.11
1.40	1438	9.25	210.89	63.3%	122.01	332.91
1.50	1388	9.88	218.01	61.3%	137.70	355.71
1.60	1337	10.51	224.06	59.2%	154.45	378.51
1.70	1287	11.15	229.06	57.1%	172.26	401.31
1.80	1236	11.78	232.99	54.9%	191.13	424.12
1.90	1185	12.41	235.86	52.8%	211.05	446.92
2.00	1135	13.05	237.68	50.6%	232.04	469.72
2.10	1084	13.68	238.43	48.4%	254.09	492.52
2.20	1034	14.31	238.12	46.2%	277.20	515.32
2.30	983	14.95	236.76	44.0%	301.37	538.12
2.40	932	15.58	234.33	41.8%	326.59	560.93
2.50	882	16.21	230.85	39.5%	352.88	583.73
2.60	831	16.85	226.30	37.3%	380.23	606.53
2.70	781	17.48	220.69	35.1%	408.64	629.33
2.80	730	18.11	214.03	32.8%	438.11	652.13
2.90	679	18.75	206.30	30.6%	468.63	674.94
3.00	629	19.38	197.52	28.3%	500.22	697.74