

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1638	0.63	0.00	0.0%	7.60	7.60
0.10	1533	2.04	16.05	65.5%	8.44	24.49
0.20	1478	3.45	30.95	74.8%	10.44	41.38
0.30	1422	4.86	44.68	76.7%	13.59	58.27
0.40	1367	6.26	57.26	76.2%	17.90	75.16
0.50	1312	7.67	68.69	74.6%	23.36	92.05
0.60	1257	9.08	78.96	72.5%	29.99	108.94
0.70	1201	10.49	88.07	70.0%	37.77	125.83
0.80	1146	11.89	96.02	67.3%	46.70	142.72
0.90	1091	13.30	102.82	64.4%	56.80	159.61
1.00	1036	14.71	108.45	61.4%	68.05	176.50
1.10	980	16.12	112.94	58.4%	80.46	193.39
1.20	925	17.52	116.26	55.3%	94.02	210.28
1.30	870	18.93	118.43	52.1%	108.74	227.17
1.40	815	20.34	119.44	48.9%	124.62	244.06
1.50	759	21.75	119.30	45.7%	141.66	260.95
1.60	704	23.15	118.00	42.5%	159.85	277.85
1.70	649	24.56	115.54	39.2%	179.20	294.74
1.80	594	25.97	111.92	35.9%	199.70	311.63
1.90	539	27.38	107.15	32.6%	221.37	328.52
2.00	483	28.78	101.22	29.3%	244.19	345.41
2.10	428	30.19	94.13	26.0%	268.16	362.30
2.20	373	31.60	85.89	22.7%	293.30	379.19
2.30	318	33.01	76.49	19.3%	319.59	396.08
2.40	262	34.41	65.93	16.0%	347.03	412.97
2.50	207	35.82	54.22	12.6%	375.64	429.86
2.60	152	37.23	41.35	9.3%	405.40	446.75
2.70	97	38.64	27.32	5.9%	436.32	463.64
2.80	41	40.04	12.14	2.5%	468.39	480.53
2.90	-14	41.45	-4.21	-0.8%	501.62	497.42
3.00	-69	42.86	-21.70	-4.2%	536.01	514.31