

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	3276	1.27	0.00	0.0%	30.40	30.40
0.10	3121	2.67	32.68	50.9%	31.50	64.18
0.20	3066	4.08	64.21	65.5%	33.76	97.96
0.30	3010	5.49	94.57	71.8%	37.17	131.74
0.40	2955	6.90	123.78	74.8%	41.74	165.52
0.50	2900	8.30	151.84	76.2%	47.47	199.31
0.60	2845	9.71	178.74	76.7%	54.35	233.09
0.70	2789	11.12	204.48	76.6%	62.39	266.87
0.80	2734	12.53	229.06	76.2%	71.59	300.65
0.90	2679	13.93	252.49	75.5%	81.94	334.43
1.00	2624	15.34	274.75	74.6%	93.45	368.21
1.10	2568	16.75	295.87	73.6%	106.12	401.99
1.20	2513	18.16	315.82	72.5%	119.95	435.77
1.30	2458	19.56	334.62	71.3%	134.93	469.55
1.40	2403	20.97	352.26	70.0%	151.07	503.33
1.50	2348	22.38	368.75	68.7%	168.36	537.11
1.60	2292	23.79	384.08	67.3%	186.81	570.89
1.70	2237	25.19	398.25	65.9%	206.42	604.67
1.80	2182	26.60	411.26	64.4%	227.19	638.45
1.90	2127	28.01	423.12	62.9%	249.11	672.23
2.00	2071	29.42	433.82	61.4%	272.19	706.01
2.10	2016	30.82	443.36	59.9%	296.43	739.79
2.20	1961	32.23	451.75	58.4%	321.82	773.57
2.30	1906	33.64	458.98	56.8%	348.38	807.36
2.40	1850	35.05	465.05	55.3%	376.08	841.14
2.50	1795	36.45	469.97	53.7%	404.95	874.92
2.60	1740	37.86	473.73	52.1%	434.97	908.70
2.70	1685	39.27	476.33	50.5%	466.15	942.48
2.80	1629	40.68	477.78	48.9%	498.48	976.26
2.90	1574	42.08	478.06	47.3%	531.98	1010.04
3.00	1519	43.49	477.20	45.7%	566.62	1043.82