

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1905	2.70	0.00	0.0%	64.80	64.80
0.50	1801	6.79	94.28	57.8%	68.69	162.97
1.00	1756	10.88	183.85	70.4%	77.29	261.14
1.50	1711	14.97	268.74	74.8%	90.58	359.32
2.00	1666	19.06	348.92	76.3%	108.57	457.49
2.50	1621	23.15	424.41	76.4%	131.26	555.67
3.00	1576	27.24	495.20	75.7%	158.65	653.84
3.50	1531	31.33	561.29	74.6%	190.73	752.02
4.00	1487	35.42	622.69	73.2%	227.51	850.19
4.50	1442	39.52	679.38	71.6%	268.98	948.37
5.00	1397	43.61	731.39	69.9%	315.16	1046.54
5.50	1352	47.70	778.69	68.0%	366.03	1144.72
6.00	1307	51.79	821.30	66.1%	421.60	1242.89
6.50	1262	55.88	859.21	64.1%	481.86	1341.07
7.00	1217	59.97	892.42	62.0%	546.82	1439.24
7.50	1173	64.06	920.93	59.9%	616.48	1537.42
8.00	1128	68.15	944.75	57.8%	690.84	1635.59
8.50	1083	72.24	963.87	55.6%	769.89	1733.77
9.00	1038	76.33	978.29	53.4%	853.65	1831.94
9.50	993	80.42	988.02	51.2%	942.09	1930.12
10.00	948	84.51	993.05	49.0%	1035.24	2028.29
10.50	903	88.60	993.38	46.7%	1133.08	2126.47
11.00	859	92.69	989.02	44.5%	1235.62	2224.64
11.50	814	96.78	979.95	42.2%	1342.86	2322.82
12.00	769	100.87	966.19	39.9%	1454.80	2420.99
12.50	724	104.97	947.74	37.6%	1571.43	2519.16
13.00	679	109.06	924.58	35.3%	1692.76	2617.34
13.50	634	113.15	896.73	33.0%	1818.78	2715.51
14.00	589	117.24	864.18	30.7%	1949.51	2813.69
14.50	545	121.33	826.94	28.4%	2084.93	2911.86
15.00	500	125.42	784.99	26.1%	2225.05	3010.04