

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1534	1.13	0.00	0.0%	27.06	27.06
0.50	1468	4.44	76.84	72.0%	29.82	106.67
1.00	1428	7.76	149.57	80.3%	36.70	186.27
1.50	1389	11.08	218.18	82.1%	47.69	265.87
2.00	1350	14.39	282.67	81.8%	62.80	345.47
2.50	1310	17.71	343.04	80.7%	82.03	425.07
3.00	1271	21.03	399.29	79.1%	105.38	504.67
3.50	1232	24.34	451.43	77.3%	132.84	584.27
4.00	1192	27.66	499.45	75.2%	164.42	663.87
4.50	1153	30.98	543.36	73.1%	200.12	743.47
5.00	1114	34.29	583.14	70.8%	239.93	823.08
5.50	1074	37.61	618.81	68.6%	283.86	902.68
6.00	1035	40.93	650.36	66.2%	331.91	982.28
6.50	996	44.24	677.80	63.8%	384.08	1061.88
7.00	956	47.56	701.12	61.4%	440.36	1141.48
7.50	917	50.88	720.32	59.0%	500.77	1221.08
8.00	878	54.20	735.40	56.5%	565.29	1300.68
8.50	838	57.51	746.36	54.1%	633.92	1380.28
9.00	799	60.83	753.21	51.6%	706.68	1459.89
9.50	760	64.15	755.94	49.1%	783.55	1539.49
10.00	721	67.46	754.55	46.6%	864.53	1619.09
10.50	681	70.78	749.05	44.1%	949.64	1698.69
11.00	642	74.10	739.43	41.6%	1038.86	1778.29
11.50	603	77.41	725.69	39.1%	1132.20	1857.89
12.00	563	80.73	707.83	36.5%	1229.66	1937.49
12.50	524	84.05	685.86	34.0%	1331.24	2017.09
13.00	485	87.36	659.76	31.5%	1436.93	2096.69
13.50	445	90.68	629.56	28.9%	1546.74	2176.30
14.00	406	94.00	595.23	26.4%	1660.67	2255.90
14.50	367	97.31	556.79	23.8%	1778.71	2335.50
15.00	327	100.63	514.23	21.3%	1900.87	2415.10