

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	1418	2.21	0.00	0.0%	26.51	26.51
0.50	1360	8.34	71.24	71.1%	28.90	100.14
1.00	1327	14.48	138.95	80.0%	34.82	173.77
1.50	1293	20.62	203.14	82.1%	44.26	247.40
2.00	1260	26.75	263.80	82.2%	57.23	321.03
2.50	1226	32.89	320.95	81.3%	73.71	394.66
3.00	1192	39.02	374.57	80.0%	93.72	468.29
3.50	1159	45.16	424.67	78.4%	117.26	541.92
4.00	1125	51.30	471.24	76.6%	144.31	615.56
4.50	1091	57.43	514.29	74.6%	174.89	689.19
5.00	1058	63.57	553.82	72.6%	208.99	762.82
5.50	1024	69.70	589.83	70.5%	246.62	836.45
6.00	990	75.84	622.31	68.4%	287.77	910.08
6.50	957	81.98	651.27	66.2%	332.44	983.71
7.00	923	88.11	676.71	64.0%	380.63	1057.34
7.50	890	94.25	698.63	61.8%	432.35	1130.97
8.00	856	100.38	717.02	59.5%	487.59	1204.60
8.50	822	106.52	731.89	57.3%	546.35	1278.24
9.00	789	112.66	743.23	55.0%	608.63	1351.87
9.50	755	118.79	751.06	52.7%	674.44	1425.50
10.00	721	124.93	755.36	50.4%	743.77	1499.13
10.50	688	131.06	756.13	48.1%	816.63	1572.76
11.00	654	137.20	753.39	45.8%	893.00	1646.39
11.50	620	143.34	747.12	43.4%	972.90	1720.02
12.00	587	149.47	737.33	41.1%	1056.33	1793.65
12.50	553	155.61	724.01	38.8%	1143.27	1867.28
13.00	519	161.74	707.18	36.4%	1233.74	1940.92
13.50	486	167.88	686.82	34.1%	1327.73	2014.55
14.00	452	174.01	662.93	31.7%	1425.24	2088.18
14.50	419	180.15	635.53	29.4%	1526.28	2161.81
15.00	385	186.29	604.60	27.0%	1630.84	2235.44