

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	1660	1.27	0.00	0.0%	53.26	53.26
0.50	1589	3.31	83.22	59.8%	55.95	139.16
1.00	1558	5.36	163.12	72.5%	61.95	225.07
1.50	1526	7.40	239.70	77.1%	71.27	310.97
2.00	1494	9.45	312.96	78.9%	83.91	396.87
<b>2.50</b>	<b>1463</b>	<b>11.49</b>	<b>382.91</b>	<b>79.3%</b>	<b>99.86</b>	<b>482.77</b>
3.00	1431	13.54	449.54	79.1%	119.13	568.68
3.50	1399	15.59	512.86	78.3%	141.72	654.58
4.00	1368	17.63	572.86	77.4%	167.63	740.48
4.50	1336	19.68	629.54	76.2%	196.85	826.39
5.00	1304	21.72	682.90	74.9%	229.39	912.29
5.50	1273	23.77	732.95	73.4%	265.24	998.19
6.00	1241	25.81	779.68	71.9%	304.42	1084.09
6.50	1209	27.86	823.09	70.3%	346.90	1170.00
7.00	1178	29.90	863.19	68.7%	392.71	1255.90
7.50	1146	31.95	899.97	67.1%	441.83	1341.80
8.00	1114	33.99	933.43	65.4%	494.27	1427.71
8.50	1083	36.04	963.58	63.7%	550.03	1513.61
9.00	1051	38.08	990.41	61.9%	609.11	1599.51
9.50	1019	40.13	1013.92	60.2%	671.50	1685.42
10.00	988	42.17	1034.11	58.4%	737.20	1771.32
10.50	956	44.22	1050.99	56.6%	806.23	1857.22
11.00	924	46.26	1064.55	54.8%	878.57	1943.12
11.50	892	48.31	1074.80	53.0%	954.23	2029.03
12.00	861	50.36	1081.73	51.1%	1033.20	2114.93
12.50	829	52.40	1085.34	49.3%	1115.50	2200.83
13.00	797	54.45	1085.63	47.5%	1201.10	2286.74
13.50	766	56.49	1082.61	45.6%	1290.03	2372.64
14.00	734	58.54	1076.27	43.8%	1382.27	2458.54
14.50	702	60.58	1066.61	41.9%	1477.83	2544.44
15.00	671	62.63	1053.64	40.1%	1576.71	2630.35