

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1619	0.70	0.00	0.0%	33.66	33.66
0.50	1565	2.45	81.94	69.6%	35.87	117.81
1.00	1535	4.21	160.71	79.6%	41.25	201.96
1.50	1505	5.96	236.33	82.6%	49.78	286.11
2.00	1474	7.71	308.78	83.4%	61.48	370.26
2.50	1444	9.47	378.08	83.2%	76.33	454.41
3.00	1414	11.22	444.21	82.5%	94.35	538.56
3.50	1384	12.97	507.18	81.4%	115.53	622.71
4.00	1354	14.73	566.99	80.2%	139.87	706.86
4.50	1323	16.48	623.64	78.8%	167.37	791.01
5.00	1293	18.23	677.13	77.4%	198.03	875.16
5.50	1263	19.99	727.46	75.8%	231.85	959.31
6.00	1233	21.74	774.63	74.2%	268.83	1043.46
6.50	1203	23.49	818.63	72.6%	308.98	1127.61
7.00	1172	25.24	859.48	70.9%	352.28	1211.76
7.50	1142	27.00	897.16	69.2%	398.75	1295.91
8.00	1112	28.75	931.69	67.5%	448.37	1380.06
8.50	1082	30.50	963.05	65.8%	501.16	1464.21
9.00	1052	32.26	991.25	64.0%	557.11	1548.36
9.50	1022	34.01	1016.29	62.3%	616.22	1632.51
10.00	991	35.76	1038.17	60.5%	678.49	1716.66
10.50	961	37.52	1056.89	58.7%	743.92	1800.81
11.00	931	39.27	1072.45	56.9%	812.51	1884.96
11.50	901	41.02	1084.84	55.1%	884.26	1969.11
12.00	871	42.78	1094.08	53.3%	959.17	2053.26
12.50	840	44.53	1100.16	51.5%	1037.25	2137.41
13.00	810	46.28	1103.07	49.7%	1118.48	2221.55
13.50	780	48.04	1102.82	47.8%	1202.88	2305.70
14.00	750	49.79	1099.42	46.0%	1290.44	2389.85
14.50	720	51.54	1092.85	44.2%	1381.16	2474.00
15.00	690	53.29	1083.12	42.3%	1475.03	2558.15