

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1014	0.14	0.00	0.0%	15.79	15.79
0.50	966	0.62	50.58	73.9%	17.84	68.42
1.00	936	1.10	98.00	81.0%	23.05	121.04
1.50	906	1.58	142.26	81.9%	31.41	173.67
2.00	876	2.06	183.38	81.0%	42.92	226.30
2.50	845	2.54	221.33	79.4%	57.60	278.93
3.00	815	3.01	256.13	77.3%	75.42	331.56
3.50	785	3.49	287.78	74.9%	96.41	384.18
4.00	755	3.97	316.27	72.4%	120.54	436.81
4.50	725	4.45	341.60	69.8%	147.84	489.44
5.00	695	4.93	363.78	67.1%	178.28	542.07
5.50	665	5.41	382.81	64.4%	211.89	594.69
6.00	635	5.88	398.67	61.6%	248.65	647.32
6.50	604	6.36	411.39	58.8%	288.56	699.95
7.00	574	6.84	420.95	55.9%	331.63	752.58
7.50	544	7.32	427.35	53.1%	377.86	805.21
8.00	514	7.80	430.60	50.2%	427.24	857.83
8.50	484	8.28	430.69	47.3%	479.77	910.46
9.00	454	8.76	427.63	44.4%	535.46	963.09
9.50	424	9.23	421.41	41.5%	594.31	1015.72
10.00	393	9.71	412.04	38.6%	656.31	1068.34
10.50	363	10.19	399.51	35.6%	721.46	1120.97
11.00	333	10.67	383.82	32.7%	789.78	1173.60
11.50	303	11.15	364.98	29.8%	861.24	1226.23
12.00	273	11.63	342.99	26.8%	935.87	1278.86
12.50	243	12.10	317.84	23.9%	1013.64	1331.48
13.00	213	12.58	289.54	20.9%	1094.58	1384.11
13.50	183	13.06	258.08	18.0%	1178.66	1436.74
14.00	152	13.54	223.46	15.0%	1265.91	1489.37
14.50	122	14.02	185.69	12.0%	1356.30	1541.99
15.00	92	14.50	144.76	9.1%	1449.86	1594.62