

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1771	0.51	0.00	0.0%	46.02	46.02
0.50	1717	1.53	89.90	65.1%	48.16	138.06
1.00	1690	2.56	176.94	76.9%	53.15	230.10
1.50	1662	3.58	261.14	81.1%	61.00	322.14
2.00	1635	4.60	342.48	82.7%	71.70	414.17
2.50	1608	5.62	420.96	83.2%	85.25	506.21
3.00	1581	6.65	496.59	83.0%	101.66	598.25
3.50	1553	7.67	569.37	82.5%	120.92	690.29
4.00	1526	8.69	639.30	81.7%	143.03	782.33
4.50	1499	9.72	706.37	80.8%	168.00	874.37
5.00	1472	10.74	770.59	79.7%	195.82	966.41
5.50	1444	11.76	831.95	78.6%	226.49	1058.45
6.00	1417	12.78	890.46	77.4%	260.02	1150.49
6.50	1390	13.81	946.12	76.1%	296.40	1242.52
7.00	1363	14.83	998.93	74.9%	335.63	1334.56
7.50	1335	15.85	1048.88	73.5%	377.72	1426.60
8.00	1308	16.87	1095.98	72.2%	422.66	1518.64
8.50	1281	17.90	1140.22	70.8%	470.46	1610.68
9.00	1254	18.92	1181.62	69.4%	521.10	1702.72
9.50	1226	19.94	1220.15	68.0%	574.60	1794.76
10.00	1199	20.96	1255.84	66.6%	630.96	1886.80
10.50	1172	21.99	1288.67	65.1%	690.16	1978.84
11.00	1145	23.01	1318.65	63.7%	752.22	2070.87
11.50	1117	24.03	1345.77	62.2%	817.14	2162.91
12.00	1090	25.06	1370.05	60.8%	884.91	2254.95
12.50	1063	26.08	1391.46	59.3%	955.53	2346.99
13.00	1036	27.10	1410.03	57.8%	1029.00	2439.03
13.50	1009	28.12	1425.74	56.3%	1105.33	2531.07
14.00	981	29.15	1438.60	54.8%	1184.51	2623.11
14.50	954	30.17	1448.60	53.4%	1266.54	2715.15
15.00	927	31.19	1455.76	51.9%	1351.43	2807.18