

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	2836	4.30	0.00	0.0%	103.08	103.08
0.50	2755	10.43	144.27	57.6%	106.08	250.35
1.00	2722	16.57	285.01	71.7%	112.60	397.61
1.50	2688	22.70	422.23	77.5%	122.64	544.87
2.00	2654	28.84	555.93	80.3%	136.20	692.13
2.50	2621	34.97	686.11	81.7%	153.29	839.39
3.00	2587	41.11	812.76	82.4%	173.89	986.66
3.50	2553	47.25	935.89	82.5%	198.03	1133.92
4.00	2520	53.38	1055.50	82.4%	225.68	1281.18
4.50	2486	59.52	1171.58	82.0%	256.86	1428.44
5.00	2453	65.65	1284.15	81.5%	291.56	1575.71
5.50	2419	71.79	1393.18	80.9%	329.78	1722.97
6.00	2385	77.93	1498.70	80.1%	371.53	1870.23
6.50	2352	84.06	1600.69	79.3%	416.80	2017.49
7.00	2318	90.20	1699.16	78.5%	465.59	2164.75
7.50	2284	96.33	1794.11	77.6%	517.91	2312.02
8.00	2251	102.47	1885.53	76.7%	573.74	2459.28
8.50	2217	108.61	1973.43	75.7%	633.11	2606.54
9.00	2183	114.74	2057.81	74.7%	695.99	2753.80
9.50	2150	120.88	2138.67	73.7%	762.40	2901.06
10.00	2116	127.01	2216.00	72.7%	832.33	3048.33
10.50	2082	133.15	2289.81	71.7%	905.78	3195.59
11.00	2049	139.29	2360.10	70.6%	982.76	3342.85
11.50	2015	145.42	2426.86	69.5%	1063.25	3490.11
12.00	1982	151.56	2490.10	68.5%	1147.28	3637.38
12.50	1948	157.69	2549.82	67.4%	1234.82	3784.64
13.00	1914	163.83	2606.01	66.3%	1325.89	3931.90
13.50	1881	169.97	2658.68	65.2%	1420.48	4079.16
14.00	1847	176.10	2707.83	64.1%	1518.59	4226.42
14.50	1813	182.24	2753.46	63.0%	1620.23	4373.69
15.00	1780	188.37	2795.56	61.8%	1725.39	4520.95