

<i>T (n.m)</i>	<i>N (r.p.m.)</i>	<i>I (amps)</i>	<i>Pout(w)</i>	<i>Eff.(%)</i>	<i>Loss(w)</i>	<i>Pin(w)</i>
0.00	2271	3.04	0.00	0.0%	73.04	73.04
0.50	2195	7.95	114.95	60.2%	75.91	190.85
1.00	2162	12.86	226.36	73.3%	82.30	308.66
1.50	2128	17.77	334.23	78.4%	92.24	426.47
2.00	2094	22.68	438.57	80.6%	105.71	544.28
2.50	2060	27.59	539.38	81.5%	122.71	662.09
3.00	2027	32.50	636.65	81.6%	143.25	779.90
3.50	1993	37.40	730.38	81.4%	167.33	897.71
4.00	1959	42.31	820.58	80.8%	194.94	1015.52
4.50	1925	47.22	907.25	80.1%	226.08	1133.33
5.00	1891	52.13	990.37	79.2%	260.77	1251.14
5.50	1858	57.04	1069.97	78.2%	298.98	1368.95
6.00	1824	61.95	1146.03	77.1%	340.73	1486.76
6.50	1790	66.86	1218.55	75.9%	386.02	1604.57
7.00	1756	71.77	1287.54	74.8%	434.84	1722.38
7.50	1723	76.67	1352.99	73.5%	487.20	1840.19
8.00	1689	81.58	1414.91	72.3%	543.09	1958.00
8.50	1655	86.49	1473.29	71.0%	602.52	2075.81
9.00	1621	91.40	1528.13	69.7%	665.48	2193.62
9.50	1588	96.31	1579.44	68.3%	731.98	2311.43
10.00	1554	101.22	1627.22	67.0%	802.02	2429.24
10.50	1520	106.13	1671.46	65.6%	875.58	2547.05
11.00	1486	111.04	1712.17	64.2%	952.69	2664.86
11.50	1453	115.94	1749.34	62.9%	1033.33	2782.67
12.00	1419	120.85	1782.97	61.5%	1117.50	2900.48
12.50	1385	125.76	1813.07	60.1%	1205.21	3018.29
13.00	1351	130.67	1839.64	58.7%	1296.46	3136.09
13.50	1318	135.58	1862.66	57.2%	1391.24	3253.90
14.00	1284	140.49	1882.16	55.8%	1489.56	3371.71
14.50	1250	145.40	1898.12	54.4%	1591.41	3489.52
15.00	1216	150.31	1910.54	53.0%	1696.79	3607.33