

<i>T (n.m)</i>	<i>N (r.p.m.)</i>	<i>I (amps)</i>	<i>Pout(w)</i>	<i>Eff.(%)</i>	<i>Loss(w)</i>	<i>Pin(w)</i>
0.00	2552	1.53	0.00	0.0%	61.03	61.03
0.50	2476	4.84	129.66	66.9%	64.03	193.70
1.00	2437	8.16	255.21	78.2%	71.16	326.36
1.50	2398	11.48	376.64	82.0%	82.40	459.03
2.00	2358	14.79	493.95	83.5%	97.75	591.70
2.50	2319	18.11	607.14	83.8%	117.23	724.37
3.00	2280	21.43	716.22	83.6%	140.82	857.04
3.50	2240	24.74	821.18	83.0%	168.53	989.71
4.00	2201	28.06	922.02	82.1%	200.36	1122.38
4.50	2162	31.38	1018.74	81.2%	236.30	1255.05
5.00	2123	34.69	1111.35	80.1%	276.37	1387.71
5.50	2083	38.01	1199.84	78.9%	320.54	1520.38
6.00	2044	41.33	1284.21	77.7%	368.84	1653.05
6.50	2005	44.64	1364.46	76.4%	421.26	1785.72
7.00	1965	47.96	1440.60	75.1%	477.79	1918.39
7.50	1926	51.28	1512.62	73.7%	538.44	2051.06
8.00	1887	54.59	1580.52	72.4%	603.20	2183.73
8.50	1847	57.91	1644.31	71.0%	672.08	2316.39
9.00	1808	61.23	1703.98	69.6%	745.09	2449.06
9.50	1769	64.54	1759.53	68.2%	822.20	2581.73
10.00	1729	67.86	1810.96	66.7%	903.44	2714.40
10.50	1690	71.18	1858.28	65.3%	988.79	2847.07
11.00	1651	74.49	1901.48	63.8%	1078.26	2979.74
11.50	1611	77.81	1940.56	62.3%	1171.85	3112.41
12.00	1572	81.13	1975.52	60.9%	1269.55	3245.07
12.50	1533	84.44	2006.37	59.4%	1371.38	3377.74
13.00	1493	87.76	2033.10	57.9%	1477.32	3510.41
13.50	1454	91.08	2055.71	56.4%	1587.37	3643.08
14.00	1415	94.39	2074.20	54.9%	1701.55	3775.75
14.50	1375	97.71	2088.58	53.4%	1819.84	3908.42
15.00	1336	101.03	2098.84	51.9%	1942.25	4041.09