

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1895	1.27	0.00	0.0%	60.87	60.87
0.50	1824	3.31	95.49	60.0%	63.56	159.04
1.00	1792	5.36	187.66	73.0%	69.56	257.22
1.50	1760	7.40	276.51	77.8%	78.88	355.39
2.00	1729	9.45	362.05	79.8%	91.52	453.57
2.50	1697	11.49	444.27	80.5%	107.47	551.74
3.00	1665	13.54	523.18	80.5%	126.74	649.92
3.50	1634	15.59	598.76	80.0%	149.33	748.09
4.00	1602	17.63	671.03	79.3%	175.23	846.27
4.50	1570	19.68	739.98	78.4%	204.46	944.44
5.00	1539	21.72	805.62	77.3%	237.00	1042.62
5.50	1507	23.77	867.94	76.1%	272.85	1140.79
6.00	1475	25.81	926.94	74.8%	312.02	1238.97
6.50	1444	27.86	982.63	73.5%	354.51	1337.14
7.00	1412	29.90	1035.00	72.1%	400.32	1435.32
7.50	1380	31.95	1084.05	70.7%	449.44	1533.49
8.00	1349	33.99	1129.78	69.2%	501.88	1631.66
8.50	1317	36.04	1172.20	67.8%	557.64	1729.84
9.00	1285	38.08	1211.30	66.3%	616.71	1828.01
9.50	1254	40.13	1247.08	64.7%	679.10	1926.19
10.00	1222	42.17	1279.55	63.2%	744.81	2024.36
10.50	1190	44.22	1308.70	61.7%	813.84	2122.54
11.00	1159	46.26	1334.54	60.1%	886.18	2220.71
11.50	1127	48.31	1357.05	58.5%	961.84	2318.89
12.00	1095	50.36	1376.25	56.9%	1040.81	2417.06
12.50	1064	52.40	1392.13	55.3%	1123.10	2515.24
13.00	1032	54.45	1404.70	53.7%	1208.71	2613.41
13.50	1000	56.49	1413.95	52.1%	1297.64	2711.59
14.00	968	58.54	1419.88	50.5%	1389.88	2809.76
14.50	937	60.58	1422.49	48.9%	1485.44	2907.94
15.00	905	62.63	1421.79	47.3%	1584.32	3006.11