

<i>T (n.m)</i>	<i>N (r.p.m.)</i>	<i>I (amps)</i>	<i>Pout(w)</i>	<i>Eff.(%)</i>	<i>Loss(w)</i>	<i>Pin(w)</i>
0.00	1769	0.67	0.00	0.0%	40.50	40.50
0.50	1720	2.21	90.05	67.9%	42.49	132.54
1.00	1693	3.74	177.33	79.0%	47.25	224.57
1.50	1667	5.28	261.85	82.7%	54.77	316.61
2.00	1641	6.81	343.60	84.1%	65.06	408.65
2.50	1614	8.34	422.58	84.4%	78.11	500.69
3.00	1588	9.88	498.80	84.2%	93.93	592.73
3.50	1561	11.41	572.25	83.6%	112.52	684.77
4.00	1535	12.95	642.94	82.8%	133.87	776.81
4.50	1508	14.48	710.86	81.8%	157.99	868.85
5.00	1482	16.01	776.01	80.8%	184.87	960.89
5.50	1456	17.55	838.40	79.6%	214.52	1052.92
6.00	1429	19.08	898.03	78.4%	246.94	1144.96
6.50	1403	20.62	954.89	77.2%	282.12	1237.00
7.00	1376	22.15	1008.98	75.9%	320.06	1329.04
7.50	1350	23.68	1060.30	74.6%	360.78	1421.08
8.00	1324	25.22	1108.86	73.3%	404.25	1513.12
8.50	1297	26.75	1154.66	71.9%	450.50	1605.16
9.00	1271	28.29	1197.69	70.6%	499.51	1697.20
9.50	1244	29.82	1237.95	69.2%	551.28	1789.24
10.00	1218	31.35	1275.45	67.8%	605.83	1881.27
10.50	1192	32.89	1310.18	66.4%	663.13	1973.31
11.00	1165	34.42	1342.15	65.0%	723.21	2065.35
11.50	1139	35.96	1371.35	63.6%	786.05	2157.39
12.00	1112	37.49	1397.78	62.1%	851.65	2249.43
12.50	1086	39.02	1421.45	60.7%	920.02	2341.47
13.00	1059	40.56	1442.35	59.3%	991.16	2433.51
13.50	1033	42.09	1460.49	57.8%	1065.06	2525.55
14.00	1007	43.63	1475.86	56.4%	1141.73	2617.58
14.50	980	45.16	1488.46	54.9%	1221.16	2709.62
15.00	954	46.69	1498.30	53.5%	1303.36	2801.66