

<i>T (n.m)</i>	<i>N (r.p.m.)</i>	<i>I (amps)</i>	<i>Pout(w)</i>	<i>Eff.(%)</i>	<i>Loss(w)</i>	<i>Pin(w)</i>
0.00	1730	0.33	0.00	0.0%	36.00	36.00
0.50	1680	1.15	87.97	69.8%	38.02	125.99
1.00	1653	1.96	173.06	80.1%	42.92	215.98
1.50	1625	2.78	255.27	83.4%	50.71	305.98
2.00	1598	3.60	334.59	84.5%	61.38	395.97
2.50	1570	4.42	411.03	84.6%	74.93	485.97
3.00	1542	5.24	484.58	84.1%	91.38	575.96
3.50	1515	6.05	555.25	83.4%	110.70	665.95
4.00	1487	6.87	623.04	82.4%	132.91	755.95
4.50	1460	7.69	687.94	81.3%	158.00	845.94
5.00	1432	8.51	749.95	80.1%	185.98	935.93
5.50	1405	9.33	809.09	78.9%	216.84	1025.93
6.00	1377	10.14	865.33	77.5%	250.59	1115.92
6.50	1350	10.96	918.70	76.2%	287.22	1205.91
7.00	1322	11.78	969.18	74.8%	326.73	1295.91
7.50	1295	12.60	1016.77	73.4%	369.13	1385.90
8.00	1267	13.42	1061.48	71.9%	414.41	1475.89
8.50	1240	14.24	1103.31	70.5%	462.58	1565.89
9.00	1212	15.05	1142.25	69.0%	513.63	1655.88
9.50	1184	15.87	1178.31	67.5%	567.57	1745.87
10.00	1157	16.69	1211.48	66.0%	624.39	1835.87
10.50	1129	17.51	1241.77	64.5%	684.09	1925.86
11.00	1102	18.33	1269.18	63.0%	746.68	2015.86
11.50	1074	19.14	1293.70	61.4%	812.15	2105.85
12.00	1047	19.96	1315.33	59.9%	880.51	2195.84
12.50	1019	20.78	1334.09	58.4%	951.75	2285.84
13.00	992	21.60	1349.96	56.8%	1025.87	2375.83
13.50	964	22.42	1362.94	55.3%	1102.88	2465.82
14.00	937	23.23	1373.04	53.7%	1182.78	2555.82
14.50	909	24.05	1380.25	52.2%	1265.56	2645.81
15.00	881	24.87	1384.59	50.6%	1351.22	2735.80