

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1756	0.25	0.00	0.0%	45.59	45.59
0.50	1698	0.76	88.91	65.0%	47.86	136.78
1.00	1669	1.27	174.79	76.7%	53.17	227.96
1.50	1640	1.77	257.65	80.7%	61.50	319.14
2.00	1611	2.28	337.47	82.2%	72.86	410.33
2.50	1582	2.79	414.27	82.6%	87.25	501.51
3.00	1553	3.29	488.03	82.3%	104.66	592.70
3.50	1525	3.80	558.77	81.7%	125.11	683.88
4.00	1496	4.31	626.47	80.8%	148.59	775.06
4.50	1467	4.81	691.15	79.8%	175.10	866.25
5.00	1438	5.32	752.80	78.6%	204.63	957.43
5.50	1409	5.83	811.42	77.4%	237.20	1048.62
6.00	1380	6.33	867.01	76.1%	272.79	1139.80
6.50	1351	6.84	919.57	74.7%	311.42	1230.98
7.00	1322	7.35	969.10	73.3%	353.07	1322.17
7.50	1293	7.85	1015.60	71.9%	397.75	1413.35
8.00	1264	8.36	1059.07	70.4%	445.47	1504.54
8.50	1235	8.87	1099.51	68.9%	496.21	1595.72
9.00	1206	9.37	1136.93	67.4%	549.98	1686.90
9.50	1177	9.88	1171.31	65.9%	606.78	1778.09
10.00	1148	10.38	1202.66	64.3%	666.61	1869.27
10.50	1120	10.89	1230.99	62.8%	729.47	1960.46
11.00	1091	11.40	1256.28	61.2%	795.36	2051.64
11.50	1062	11.90	1278.55	59.7%	864.27	2142.82
12.00	1033	12.41	1297.79	58.1%	936.22	2234.01
12.50	1004	12.92	1314.00	56.5%	1011.20	2325.19
13.00	975	13.42	1327.17	54.9%	1089.20	2416.38
13.50	946	13.93	1337.32	53.3%	1170.24	2507.56
14.00	917	14.44	1344.44	51.7%	1254.30	2598.74
14.50	888	14.94	1348.53	50.1%	1341.39	2689.93
15.00	859	15.45	1349.59	48.5%	1431.52	2781.11