

<i>T (n.m)</i>	<i>N (r.p.m.)</i>	<i>I (amps)</i>	<i>Pout(w)</i>	<i>Eff.(%)</i>	<i>Loss(w)</i>	<i>Pin(w)</i>
0.00	2128	0.33	0.00	0.0%	59.79	59.79
0.50	2076	0.95	108.71	63.8%	61.80	170.51
1.00	2051	1.56	214.82	76.4%	66.42	281.24
1.50	2026	2.18	318.32	81.2%	73.64	391.96
2.00	2002	2.79	419.21	83.4%	83.48	502.68
2.50	1977	3.41	517.48	84.4%	95.92	613.41
3.00	1952	4.02	613.15	84.7%	110.98	724.13
3.50	1927	4.64	706.22	84.6%	128.64	834.85
4.00	1902	5.25	796.67	84.3%	148.91	945.58
4.50	1877	5.87	884.51	83.7%	171.79	1056.30
5.00	1852	6.48	969.75	83.1%	197.28	1167.02
5.50	1827	7.10	1052.37	82.4%	225.37	1277.75
6.00	1802	7.71	1132.39	81.6%	256.08	1388.47
6.50	1777	8.33	1209.80	80.7%	289.40	1499.20
7.00	1752	8.94	1284.60	79.8%	325.32	1609.92
7.50	1728	9.56	1356.79	78.9%	363.85	1720.64
8.00	1703	10.17	1426.37	77.9%	404.99	1831.37
8.50	1678	10.79	1493.34	76.9%	448.75	1942.09
9.00	1653	11.40	1557.71	75.9%	495.10	2052.81
9.50	1628	12.02	1619.46	74.9%	544.07	2163.54
10.00	1603	12.63	1678.61	73.8%	595.65	2274.26
10.50	1578	13.25	1735.15	72.8%	649.84	2384.98
11.00	1553	13.87	1789.07	71.7%	706.63	2495.71
11.50	1528	14.48	1840.39	70.6%	766.03	2606.43
12.00	1503	15.10	1889.11	69.5%	828.05	2717.15
12.50	1478	15.71	1935.21	68.4%	892.67	2827.88
13.00	1453	16.33	1978.70	67.3%	959.90	2938.60
13.50	1429	16.94	2019.58	66.2%	1029.74	3049.32
14.00	1404	17.56	2057.86	65.1%	1102.19	3160.05
14.50	1379	18.17	2093.53	64.0%	1177.24	3270.77
15.00	1354	18.79	2126.58	62.9%	1254.91	3381.49