

<i>T (n.m)</i>	<i>N (r.p.m.)</i>	<i>I (amps)</i>	<i>Pout(w)</i>	<i>Eff.(%)</i>	<i>Loss(w)</i>	<i>Pin(w)</i>
0.00	2359	0.37	0.00	0.0%	66.27	66.27
0.50	2299	1.05	120.39	63.7%	68.59	188.99
1.00	2270	1.73	237.76	76.3%	73.94	311.70
1.50	2242	2.41	352.11	81.1%	82.31	434.42
2.00	2213	3.10	463.44	83.2%	93.70	557.14
2.50	2184	3.78	571.74	84.1%	108.12	679.86
3.00	2155	4.46	677.03	84.4%	125.55	802.58
3.50	2126	5.14	779.29	84.2%	146.01	925.30
4.00	2097	5.82	878.53	83.8%	169.49	1048.02
4.50	2068	6.50	974.75	83.3%	195.99	1170.73
5.00	2040	7.19	1067.95	82.6%	225.51	1293.45
5.50	2011	7.87	1158.12	81.8%	258.05	1416.17
6.00	1982	8.55	1245.28	80.9%	293.61	1538.89
6.50	1953	9.23	1329.41	80.0%	332.20	1661.61
7.00	1924	9.91	1410.52	79.1%	373.81	1784.33
7.50	1895	10.59	1488.61	78.1%	418.44	1907.04
8.00	1867	11.28	1563.68	77.0%	466.09	2029.76
8.50	1838	11.96	1635.72	76.0%	516.76	2152.48
9.00	1809	12.64	1704.75	74.9%	570.45	2275.20
9.50	1780	13.32	1770.75	73.8%	627.17	2397.92
10.00	1751	14.00	1833.73	72.7%	686.91	2520.64
10.50	1722	14.69	1893.69	71.6%	749.66	2643.36
11.00	1693	15.37	1950.63	70.5%	815.44	2766.07
11.50	1665	16.05	2004.55	69.4%	884.25	2888.79
12.00	1636	16.73	2055.44	68.3%	956.07	3011.51
12.50	1607	17.41	2103.31	67.1%	1030.91	3134.23
13.00	1578	18.09	2148.17	66.0%	1108.78	3256.95
13.50	1549	18.78	2190.00	64.8%	1189.67	3379.67
14.00	1520	19.46	2228.81	63.6%	1273.58	3502.38
14.50	1491	20.14	2264.59	62.5%	1360.51	3625.10
15.00	1463	20.82	2297.36	61.3%	1450.46	3747.82