

<i>T (n.m)</i>	<i>N (r.p.m.)</i>	<i>I (amps)</i>	<i>Pout(w)</i>	<i>Eff.(%)</i>	<i>Loss(w)</i>	<i>Pin(w)</i>
0.00	1923	0.40	0.00	0.0%	44.00	44.00
0.50	1866	1.31	97.69	67.8%	46.30	143.99
1.00	1835	2.22	192.17	78.8%	51.82	243.98
1.50	1804	3.13	283.44	82.4%	60.53	343.98
2.00	1774	4.04	371.51	83.7%	72.45	443.97
2.50	1743	4.95	456.38	83.9%	87.58	543.96
3.00	1713	5.85	538.04	83.6%	105.91	643.95
3.50	1682	6.76	616.50	82.9%	127.45	743.95
4.00	1651	7.67	691.75	82.0%	152.19	843.94
4.50	1621	8.58	763.80	80.9%	180.13	943.93
5.00	1590	9.49	832.64	79.8%	211.28	1043.93
5.50	1560	10.40	898.28	78.5%	245.64	1143.92
6.00	1529	11.31	960.71	77.2%	283.20	1243.91
6.50	1498	12.22	1019.94	75.9%	323.96	1343.90
7.00	1468	13.13	1075.97	74.5%	367.93	1443.90
7.50	1437	14.04	1128.78	73.1%	415.10	1543.89
8.00	1407	14.94	1178.40	71.7%	465.48	1643.88
8.50	1376	15.85	1224.81	70.2%	519.07	1743.87
9.00	1345	16.76	1268.01	68.8%	575.85	1843.87
9.50	1315	17.67	1308.01	67.3%	635.85	1943.86
10.00	1284	18.58	1344.81	65.8%	699.04	2043.85
10.50	1254	19.49	1378.40	64.3%	765.45	2143.85
11.00	1223	20.40	1408.79	62.8%	835.05	2243.84
11.50	1192	21.31	1435.97	61.3%	907.86	2343.83
12.00	1162	22.22	1459.94	59.7%	983.88	2443.82
12.50	1131	23.13	1480.72	58.2%	1063.10	2543.82
13.00	1101	24.03	1498.28	56.7%	1145.53	2643.81
13.50	1070	24.94	1512.65	55.1%	1231.16	2743.80
14.00	1039	25.85	1523.80	53.6%	1319.99	2843.80
14.50	1009	26.76	1531.76	52.0%	1412.03	2943.79
15.00	978	27.67	1536.50	50.5%	1507.28	3043.78