

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	3370	0.82	0.00	0.0%	122.72	122.72
0.50	3295	1.99	172.54	57.9%	125.49	298.03
1.00	3264	3.16	341.82	72.2%	131.52	473.34
1.50	3233	4.32	507.84	78.3%	140.82	648.65
2.00	3202	5.49	670.60	81.4%	153.37	823.97
2.50	3171	6.66	830.09	83.1%	169.19	999.28
3.00	3140	7.83	986.33	84.0%	188.26	1174.59
3.50	3108	9.00	1139.30	84.4%	210.60	1349.90
4.00	3077	10.17	1289.01	84.5%	236.20	1525.22
4.50	3046	11.34	1435.47	84.4%	265.06	1700.53
5.00	3015	12.51	1578.66	84.2%	297.18	1875.84
5.50	2984	13.67	1718.59	83.8%	332.56	2051.15
6.00	2953	14.84	1855.26	83.3%	371.20	2226.46
6.50	2922	16.01	1988.67	82.8%	413.11	2401.78
7.00	2890	17.18	2118.81	82.2%	458.27	2577.09
7.50	2859	18.35	2245.70	81.6%	506.70	2752.40
8.00	2828	19.52	2369.33	80.9%	558.38	2927.71
8.50	2797	20.69	2489.69	80.2%	613.33	3103.02
9.00	2766	21.86	2606.80	79.5%	671.54	3278.34
9.50	2735	23.02	2720.64	78.8%	733.01	3453.65
10.00	2704	24.19	2831.22	78.0%	797.74	3628.96
10.50	2672	25.36	2938.54	77.2%	865.73	3804.27
11.00	2641	26.53	3042.60	76.5%	936.98	3979.58
11.50	2610	27.70	3143.40	75.7%	1011.50	4154.90
12.00	2579	28.87	3240.94	74.8%	1089.27	4330.21
12.50	2548	30.04	3335.21	74.0%	1170.31	4505.52
13.00	2517	31.21	3426.23	73.2%	1254.60	4680.83
13.50	2486	32.37	3513.98	72.4%	1342.16	4856.14
14.00	2454	33.54	3598.48	71.5%	1432.98	5031.46
14.50	2423	34.71	3679.71	70.7%	1527.06	5206.77
15.00	2392	35.88	3757.68	69.8%	1624.40	5382.08