

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	1750	1.96	0.00	0.0%	23.56	23.56
0.50	1639	9.52	85.81	75.1%	28.38	114.18
1.00	1566	17.07	163.97	80.1%	40.84	204.81
1.50	1493	24.62	234.49	79.4%	60.94	295.43
2.00	1420	32.17	297.36	77.0%	88.69	386.05
2.50	1347	39.72	352.59	74.0%	124.08	476.68
3.00	1274	47.27	400.18	70.5%	167.12	567.30
3.50	1201	54.83	440.12	66.9%	217.80	657.92
4.00	1128	62.38	472.42	63.1%	276.13	748.54
4.50	1055	69.93	497.07	59.2%	342.10	839.17
5.00	982	77.48	514.08	55.3%	415.71	929.79
5.50	909	85.03	523.45	51.3%	496.97	1020.41
6.00	836	92.59	525.17	47.3%	585.87	1111.04
6.50	763	100.14	519.24	43.2%	682.42	1201.66
7.00	690	107.69	505.68	39.1%	786.61	1292.28
7.50	617	115.24	484.46	35.0%	898.44	1382.90
8.00	544	122.79	455.61	30.9%	1017.92	1473.53
8.50	471	130.35	419.11	26.8%	1145.04	1564.15
9.00	398	137.90	374.96	22.7%	1279.81	1654.77
9.50	325	145.45	323.18	18.5%	1422.22	1745.40
10.00	252	153.00	263.74	14.4%	1572.28	1836.02
10.50	179	160.55	196.67	10.2%	1729.98	1926.64
11.00	106	168.11	121.94	6.0%	1895.32	2017.26
11.50	33	175.66	39.58	1.9%	2068.31	2107.89
12.00	-40	183.21	-50.43	-2.3%	2248.94	2198.51
12.50	-113	190.76	-148.08	-6.5%	2437.22	2289.13
13.00	-186	198.31	-253.38	-10.6%	2633.14	2379.76
13.50	-259	205.86	-366.32	-14.8%	2836.70	2470.38
14.00	-332	213.42	-486.91	-19.0%	3047.91	2561.00
14.50	-405	220.97	-615.14	-23.2%	3266.77	2651.63
15.00	-478	228.52	-751.02	-27.4%	3493.26	2742.25
1.61	1477	26.28	248.98	78.9%	66.39	315.37