

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1092	0.38	0.00	0.0%	9.06	9.06
0.50	1008	2.74	52.80	80.4%	12.90	65.70
1.00	945	5.10	98.98	80.9%	23.36	122.34
1.50	882	7.46	138.54	77.4%	40.44	178.98
2.00	819	9.82	171.48	72.8%	64.13	235.62
2.50	756	12.18	197.81	67.7%	94.45	292.26
3.00	692	14.54	217.51	62.3%	131.39	348.90
3.50	629	16.90	230.60	56.9%	174.94	405.54
4.00	566	19.26	237.06	51.3%	225.12	462.18
4.50	503	21.62	236.91	45.7%	281.91	518.82
5.00	440	23.98	230.13	40.0%	345.32	575.46
5.50	376	26.34	216.74	34.3%	415.35	632.09
6.00	313	28.70	196.73	28.6%	492.00	688.73
6.50	250	31.06	170.10	22.8%	575.28	745.37
7.00	187	33.42	136.85	17.1%	665.17	802.01
7.50	123	35.78	96.98	11.3%	761.67	858.65
8.00	60	38.14	50.49	5.5%	864.80	915.29
8.50	-3	40.50	-2.62	-0.3%	974.55	971.93
9.00	-66	42.86	-62.35	-6.1%	1090.92	1028.57
9.50	-129	45.22	-128.69	-11.9%	1213.90	1085.21
10.00	-193	47.58	-201.66	-17.7%	1343.51	1141.85
10.50	-256	49.94	-281.25	-23.5%	1479.73	1198.49
11.00	-319	52.30	-367.45	-29.3%	1622.58	1255.13
11.50	-382	54.66	-460.27	-35.1%	1772.04	1311.77
12.00	-445	57.02	-559.72	-40.9%	1928.12	1368.41
12.50	-509	59.38	-665.78	-46.7%	2090.83	1425.04
13.00	-572	61.74	-778.46	-52.5%	2260.15	1481.68
13.50	-635	64.10	-897.76	-58.4%	2436.09	1538.32
14.00	-698	66.46	-1023.68	-64.2%	2618.65	1594.96
14.50	-761	68.82	-1156.22	-70.0%	2807.83	1651.60
15.00	-825	71.18	-1295.38	-75.8%	3003.62	1708.24