

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	2495	1.83	0.00	0.0%	44.02	44.02
0.50	2385	7.23	124.88	72.0%	48.59	173.48
1.00	2320	12.62	242.93	80.2%	60.01	302.94
1.50	2255	18.02	354.15	81.9%	78.25	432.40
2.00	2189	23.41	458.54	81.6%	103.33	561.86
2.50	2124	28.81	556.09	80.4%	135.23	691.32
3.00	2059	34.20	646.81	78.8%	173.98	820.78
3.50	1994	39.59	730.69	76.9%	219.55	950.25
4.00	1928	44.99	807.75	74.8%	271.96	1079.71
4.50	1863	50.38	877.97	72.6%	331.20	1209.17
5.00	1798	55.78	941.36	70.3%	397.27	1338.63
5.50	1733	61.17	997.91	68.0%	470.18	1468.09
6.00	1667	66.56	1047.63	65.6%	549.92	1597.55
6.50	1602	71.96	1090.52	63.1%	636.49	1727.01
7.00	1537	77.35	1126.58	60.7%	729.89	1856.47
7.50	1472	82.75	1155.80	58.2%	830.13	1985.94
8.00	1406	88.14	1178.20	55.7%	937.20	2115.40
8.50	1341	93.54	1193.75	53.2%	1051.10	2244.86
9.00	1276	98.93	1202.48	50.6%	1171.84	2374.32
9.50	1211	104.32	1204.37	48.1%	1299.41	2503.78
10.00	1145	109.72	1199.43	45.5%	1433.81	2633.24
10.50	1080	115.11	1187.66	43.0%	1575.04	2762.70
11.00	1015	120.51	1169.05	40.4%	1723.11	2892.16
11.50	950	125.90	1143.62	37.8%	1878.01	3021.63
12.00	884	131.30	1111.34	35.3%	2039.74	3151.09
12.50	819	136.69	1072.24	32.7%	2208.31	3280.55
13.00	754	142.08	1026.30	30.1%	2383.71	3410.01
13.50	689	147.48	973.53	27.5%	2565.94	3539.47
14.00	623	152.87	913.93	24.9%	2755.00	3668.93
14.50	558	158.27	847.50	22.3%	2950.90	3798.39
15.00	493	163.66	774.23	19.7%	3153.63	3927.85