

<i>T (n.m)</i>	<i>N (r.p.m.)</i>	<i>I (amps)</i>	<i>Pout(w)</i>	<i>Eff.(%)</i>	<i>Loss(w)</i>	<i>Pin(w)</i>
0.00	1941	1.17	0.00	0.0%	28.19	28.19
0.50	1843	5.37	96.49	74.9%	32.40	128.89
1.00	1780	9.57	186.40	81.2%	43.18	229.58
1.50	1717	13.76	269.74	81.7%	60.53	330.27
2.00	1654	17.96	346.51	80.4%	84.45	430.96
2.50	1592	22.15	416.71	78.4%	114.94	531.65
3.00	1529	26.35	480.34	76.0%	152.01	632.35
3.50	1466	30.54	537.39	73.3%	195.64	733.04
4.00	1403	34.74	587.88	70.5%	245.85	833.73
4.50	1341	38.93	631.79	67.6%	302.63	934.42
5.00	1278	43.13	669.13	64.6%	365.99	1035.11
5.50	1215	47.33	699.90	61.6%	435.91	1135.81
6.00	1152	51.52	724.09	58.6%	512.41	1236.50
6.50	1090	55.72	741.72	55.5%	595.47	1337.19
7.00	1027	59.91	752.77	52.4%	685.11	1437.88
7.50	964	64.11	757.25	49.2%	781.33	1538.57
8.00	901	68.30	755.16	46.1%	884.11	1639.27
8.50	839	72.50	746.50	42.9%	993.46	1739.96
9.00	776	76.69	731.26	39.7%	1109.39	1840.65
9.50	713	80.89	709.45	36.5%	1231.89	1941.34
10.00	650	85.08	681.07	33.4%	1360.96	2042.04
10.50	588	89.28	646.12	30.2%	1496.60	2142.73
11.00	525	93.48	604.60	27.0%	1638.82	2243.42
11.50	462	97.67	556.51	23.7%	1787.60	2344.11
12.00	399	101.87	501.84	20.5%	1942.96	2444.80
12.50	337	106.06	440.60	17.3%	2104.89	2545.50
13.00	274	110.26	372.79	14.1%	2273.39	2646.19
13.50	211	114.45	298.41	10.9%	2448.47	2746.88
14.00	148	118.65	217.46	7.6%	2630.11	2847.57
14.50	86	122.84	129.93	4.4%	2818.33	2948.26
15.00	23	127.04	35.84	1.2%	3013.12	3048.96