

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	1454	0.63	0.00	0.0%	15.10	15.10
0.50	1371	3.78	71.78	79.2%	18.84	90.62
1.00	1311	6.92	137.34	82.7%	28.81	166.14
1.50	1252	10.07	196.66	81.4%	45.00	241.66
2.00	1193	13.22	249.76	78.7%	67.42	317.18
2.50	1133	16.36	296.63	75.5%	96.07	392.70
3.00	1074	19.51	337.28	72.0%	130.94	468.22
3.50	1014	22.66	371.69	68.4%	172.04	543.74
4.00	955	25.80	399.88	64.6%	219.38	619.26
4.50	895	28.95	421.84	60.7%	272.94	694.78
5.00	836	32.10	437.57	56.8%	332.72	770.29
5.50	776	35.24	447.08	52.9%	398.74	845.81
6.00	717	38.39	450.35	48.9%	470.98	921.33
6.50	657	41.54	447.40	44.9%	549.45	996.85
7.00	598	44.68	438.22	40.9%	634.15	1072.37
7.50	538	47.83	422.81	36.8%	725.07	1147.89
8.00	479	50.98	401.18	32.8%	822.23	1223.41
8.50	419	54.12	373.32	28.7%	925.61	1298.93
9.00	360	57.27	339.23	24.7%	1035.22	1374.45
9.50	300	60.42	298.91	20.6%	1151.06	1449.97
10.00	241	63.56	252.36	16.5%	1273.12	1525.48
10.50	182	66.71	199.59	12.5%	1401.42	1601.00
11.00	122	69.86	140.59	8.4%	1535.94	1676.52
11.50	63	73.00	75.36	4.3%	1676.68	1752.04
12.00	3	76.15	3.90	0.2%	1823.66	1827.56
12.50	-56	79.30	-73.79	-3.9%	1976.87	1903.08
13.00	-116	82.44	-157.70	-8.0%	2136.30	1978.60
13.50	-175	85.59	-247.84	-12.1%	2301.96	2054.12
14.00	-235	88.73	-344.21	-16.2%	2473.85	2129.64
14.50	-294	91.88	-446.80	-20.3%	2651.96	2205.16
15.00	-354	95.03	-555.63	-24.4%	2836.30	2280.68