

<b>T (n.m)</b>	<b>N (r.p.m.)</b>	<b>I (amps)</b>	<b>Pout(w)</b>	<b>Eff.(%)</b>	<b>Loss(w)</b>	<b>Pin(w)</b>
0.00	1342	0.58	0.00	0.0%	13.94	13.94
0.50	1265	3.49	66.26	79.2%	17.39	83.65
1.00	1211	6.39	126.77	82.7%	26.59	153.36
1.50	1156	9.29	181.54	81.4%	41.54	223.07
2.00	1101	12.20	230.55	78.7%	62.23	292.78
2.50	1046	15.10	273.82	75.5%	88.68	362.49
3.00	991	18.01	311.33	72.0%	120.87	432.20
3.50	936	20.91	343.10	68.4%	158.81	501.91
4.00	881	23.82	369.12	64.6%	202.50	571.62
4.50	826	26.72	389.39	60.7%	251.94	641.33
5.00	771	29.63	403.91	56.8%	307.13	711.04
5.50	717	32.53	412.69	52.9%	368.07	780.75
6.00	662	35.44	415.71	48.9%	434.75	850.46
6.50	607	38.34	412.99	44.9%	507.18	920.17
7.00	552	41.25	404.51	40.9%	585.37	989.88
7.50	497	44.15	390.29	36.8%	669.30	1059.59
8.00	442	47.05	370.32	32.8%	758.98	1129.30
8.50	387	49.96	344.60	28.7%	854.41	1199.01
9.00	332	52.86	313.13	24.7%	955.59	1268.72
9.50	277	55.77	275.92	20.6%	1062.51	1338.43
10.00	222	58.67	232.95	16.5%	1175.19	1408.14
10.50	168	61.58	184.24	12.5%	1293.61	1477.85
11.00	113	64.48	129.77	8.4%	1417.79	1547.56
11.50	58	67.39	69.56	4.3%	1547.71	1617.27
12.00	3	70.29	3.60	0.2%	1683.38	1686.98
12.50	-52	73.20	-68.11	-3.9%	1824.80	1756.69
13.00	-107	76.10	-145.57	-8.0%	1971.97	1826.40
13.50	-162	79.00	-228.77	-12.1%	2124.88	1896.11
14.00	-217	81.91	-317.73	-16.2%	2283.55	1965.82
14.50	-272	84.81	-412.43	-20.3%	2447.96	2035.53
15.00	-327	87.72	-512.89	-24.4%	2618.13	2105.24