

T (n.m)	N (r.p.m.)	I (amps)	Pout(w)	Eff.(%)	Loss(w)	Pin(w)
0.00	1745	0.38	0.00	0.0%	18.12	18.12
0.50	1645	2.27	86.14	79.2%	22.61	108.75
1.00	1574	4.15	164.80	82.7%	34.57	199.37
1.50	1502	6.04	236.00	81.4%	54.00	289.99
2.00	1431	7.93	299.72	78.7%	80.90	380.62
2.50	1360	9.82	355.96	75.5%	115.28	471.24
3.00	1288	11.71	404.73	72.0%	157.13	561.86
3.50	1217	13.59	446.03	68.4%	206.45	652.48
4.00	1146	15.48	479.86	64.6%	263.25	743.11
4.50	1074	17.37	506.21	60.7%	327.52	833.73
5.00	1003	19.26	525.09	56.8%	399.27	924.35
5.50	931	21.15	536.49	52.9%	478.48	1014.98
6.00	860	23.03	540.42	48.9%	565.18	1105.60
6.50	789	24.92	536.88	44.9%	659.34	1196.22
7.00	717	26.81	525.87	40.9%	760.98	1286.84
7.50	646	28.70	507.38	36.8%	870.09	1377.47
8.00	575	30.59	481.42	32.8%	986.67	1468.09
8.50	503	32.47	447.98	28.7%	1110.73	1558.71
9.00	432	34.36	407.07	24.7%	1242.26	1649.34
9.50	361	36.25	358.69	20.6%	1381.27	1739.96
10.00	289	38.14	302.83	16.5%	1527.75	1830.58
10.50	218	40.03	239.51	12.5%	1681.70	1921.20
11.00	146	41.91	168.70	8.4%	1843.12	2011.83
11.50	75	43.80	90.43	4.3%	2012.02	2102.45
12.00	4	45.69	4.68	0.2%	2188.39	2193.07
12.50	-68	47.58	-88.54	-3.9%	2372.24	2283.70
13.00	-139	49.46	-189.24	-8.0%	2563.56	2374.32
13.50	-210	51.35	-297.41	-12.1%	2762.35	2464.94
14.00	-282	53.24	-413.05	-16.2%	2968.61	2555.56
14.50	-353	55.13	-536.17	-20.3%	3182.35	2646.19
15.00	-424	57.02	-666.75	-24.4%	3403.56	2736.81